

SUNNYSIDE CLEAR WATERPROOFER

726



SUNNYSIDE CLEAR WATERPROOFER

DESCRIPTION

Sunnyside Clear Formula Exterior Waterproofer is a clear silicon waterproofer that protects and prevents water damage.

ITEM NUMERS & SIZES

Item Number	1-Gallon	5-Gallon
72632	726G1	726G5

HAZARDOUS INGREDIENTS

Ingredient	CAS#	Percent
No hazardous components by OSHA definition.		

PHYSICAL PROPERTIES

Typical Properties	Results
GRAVITY, (60 °F)	
API	
SPECIFIC DENSITY (Lb./GAL)	0.9993
DENSITY (Lb./GAL)	8.32
DISTILLATION RANGE	212°F.IBP
FREEZING POINT, °F (°C)	
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT, °F	
FLASH POINT, T.C.C. °F	
FLAMMABLE LIMITS IN AIR, % BY VOLUME	
LOWER, AT 100°F (38°C)	
UPPER, AT 200°F (93°C)	
AUTOIGNITION TEMPERATURE, °F (°C)	
COLOR, SAYBOLT	
DOCTOR TEST	
CORROSION, 3 HRS. @ 212 °F	
NON-VOLATILES, g/100ml	
ACIDITY	
ALKALINITY (AS NH3, WT%)	
EVAPORATION RATE	
APPEARANCE	Milky White
ODOR	Mild
VAPOR PRESSURE, mm Hg @ 20 °C	
REFRACTIVE INDEX, @ 20 °C	
SULFUR CONTENT, PPM	
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	
WATER MISCIBILITY	Complete
DOT SHIPPING NAME	Not regulated by US DOT as a hazardous material.
DOT CLASSIFICATION	
SHIPPING Wt. at 20 °C	8.32
V.O.C. (g/L)	20grams/L.

These properties are representative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

SAFETY INFORMATION

HEALTH:	1
FIRE:	0
REACTIVITY:	0

PRODUCT APPLICATION

Apply a uniform coat to provide lasting protection to a variety of surfaces, including wood, brick and concrete.

TEST METHOD

ASTM	Applied
D-1298	■
D-86	■
D-1133	
D-611	
D-56	
D-1255	
D-156	
D-484	
D-130	
D-1353	
D-847	
D-1614	
D-1296	■
D-1218	
D-1266	
D-1364	
D-1722	

See MSDS sheet for additional Health, Safety, Handling and Regulatory Information available on our website at www.sunnysidecorp.com/msds.html