

SUNNYSIDE QUALITY PRODUCTS SINCE 1893

FAST-ACTING GEL!

2 Minute Remover

The Ultimate Paint and Varnish Remover



Paints & Epoxies	Begins working	Clear Finishes & Stains	Begins working
Oil Based	2 min.	Varnish	2 min.
Latex/Acrylic	2 min.	(Alkyd-Spar)	
Enamel-Alkyd	5 min.	Shellac	2 min.
Epoxy	5 min.	Polyurethane	5 min.
Marine Finish	5 min.	Floor Finishes	5 min.

- Strips up to 25 sq. ft.
- Removes multiple layers
- Clings to vertical surfaces
- Non-flammable

Lo mejor en removedores de pintura y barniz

! DANGER! POISON!
! PELIGRO! VENENO!
 MAY BE FATAL OR CAUSE BLINDNESS
 PUEDE SER MORTAL O CAUSAR CEGERA
 IF SWALLOWED. VAPOR HARMFUL.
 SI SE INGIERE. LOS VAPORES SON NOCIVOS.
 SKIN AND EYE IRRITANT.
 IRRITA LA PIEL Y LOS OJOS.

Carefully read all cautions and HEALTH HAZARD INFORMATION elsewhere on this container. Use only as directed.

Lea atentamente todas las precauciones y la INFORMACIÓN SOBRE RIESGOS PARA LA SALUD en otras partes de este envase. Usar sólo según las instrucciones.

32 FL.OZ. (1QT.) .9463 LITER

Sunnyside 2-Minute Paint and Varnish Remover is a very powerful, fast-acting, highly effective, non-flammable paint and varnish remover. This product will remove multiple layers of paint and varnish without damaging wood, metal and masonry. Sunnyside 2-Minute Remover begins working in 2 minutes on most coatings, and will soften more difficult coatings in 5 minutes; see chart on front of container for coating type and time. Our powerful gel-type formula improves cling and cutting power on both vertical and horizontal surfaces. One gallon of remover covers approximately 100 square feet of surface area.

Directions: For your safety, read all information on this container before using. Use this product outdoors if possible. If used indoors, provide plenty of fresh air by opening all doors and windows to achieve cross ventilation. Do not use in basement or other unventilated areas.

Application: Open container carefully. Protect hands with solvent resistant gloves. Wear glasses or goggles to protect eyes. Apply a generous amount to area no larger than two feet by two feet at a time. Do not brush back and forth like paint. Allow the remover to stand undisturbed until the old finish softens enough to be removed with a putty knife. Use steel wool or a stiff brush for hard to get at places. Some finishes may require more than one application. To remove any remaining deep stain from wood, scrub with household bleach or oxalic acid solution and steel wool. Cool water and a scrub brush may be used for a final rinse. On fine wood and veneers use mineral spirits to prevent warping or raising the grain. Allow to dry thoroughly before refinishing. Rags and other waste should be allowed to completely air dry, and then disposed of in trash collection. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Caution: This product can cause damage to most materials on contact. Avoid contact with all surfaces except those being worked on. Damages rubber, asphalt tile, plastic, fiberglass, and other synthetic materials. Product should be stored in a cool place, kept tightly capped and used within six months.

Limited Guarantee: When applied and used according to label directions, if not satisfied with this product, Sunnyside will refund your purchase price with proof of purchase at the company's option. This guarantee does not include labor, cost of labor for application or any related damages.

PRODUCT QUESTIONS..?
 For more information contact us at 1-800-323-8611 or visit us on the web at www.sunnysidecorp.com.
www.sunnysidecorp.com/2minuteremover

SUNNYSIDE CORPORATION
 Consumer Products Division
 Wheeling, IL 60090-6095
 © 7/2014 S.C.



CAUTIONS: CONTAINS METHYLENE CHLORIDE, METHYL ALCOHOL, XYLENE, ETHYL BENZENE, DIPROPYLENE GLYCOL METHYL ETHER & PETROLEUM DISTILLATE. Cannot be made non-poisonous. Keep away from heat and flame. Contact with flames or hot surfaces can produce toxic gases. DO NOT smoke. Vapor harmful. Do not allow vapors to accumulate. Avoid contact with skin or eyes. Open container slowly to relieve pressure and close after each use. Do not transfer to unlabeled containers.

Health Note: Contains Methylene Chloride which has been shown to cause cancer in certain laboratory animals. Possible risk to your health depends on level and duration of exposure.

Other Health Hazards: If during use you experience discomfort such as eye watering, headache or dizziness, increase fresh air or leave the area. The use of a respirator is not recommended unless professionally supervised. Dust masks provide no protection from vapors. Persons with heart or respiratory problems should avoid use of this product. Exposure to Methylene Chloride, a component of this product, REDUCES THE BLOOD'S OXYGEN CARRYING CAPACITY. Reports have associated repeated or prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. May be harmful if absorbed through the skin.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

First Aid: If swallowed, DO NOT induce vomiting. GET IMMEDIATE MEDICAL ATTENTION! Call physician, hospital emergency room or poison control center immediately. In case of eye or skin contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Get medical attention. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention.

Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.
 California SCAQMD Rule 443.1: Max. VOC: 181 g/L; Max. Vapor Pressure: Non-Exempt VOC: 100 mm Hg; Exempt VOC: 350 mm Hg; Non-photochemically Reactive. Less than 50% VOC.

ADVERTENCIAS: CONTIENE CLORURO DE METILENO, ALCOHOL METILICO, XILENO, ETILBENCENO, ÉTER METILICO CON GLICOL DIPROPILENO Y DESTILADO DE PETRÓLEO. No es posible que no sea venenoso. Mantenga alejado del calor y el fuego. El contacto con el fuego o superficies calientes puede producir gases tóxicos. NO fume. Vapor nocivo. No permite que se acumulen vapores. Evite el contacto con los ojos o piel. Abra el envase lentamente para liberar la presión y cierre después de cada uso. No transfiera a envases sin etiqueta.

Nota sanitaria: Contiene cloruro de metileno que ha demostrado ser causante de cáncer en ciertos animales de laboratorio. El posible riesgo para su salud depende del nivel y la duración de la exposición.

Otros peligros sanitarios: Si durante el uso, experimenta molestias como por ejemplo lagrimeo en los ojos, dolor de cabeza o mareos, aumente el aire fresco o abandone el área. El uso de un respirador no es recomendado a menos que esté supervisado por un profesional. Las mascarillas antipolvo no protegen contra los vapores. Las personas con problemas cardíacos o respiratorios no deben usar este producto. La exposición al cloruro de metileno, un componente de este producto, reduce la capacidad de oxigenación de la sangre. Los informes asocian la sobreexposición laboral prolongada y continua a los disolventes con daños permanentes del cerebro y del sistema nervioso. El uso indebido intencional mediante la concentración deliberada y la inhalación de los vapores puede ser nocivo y causar la muerte. Puede ser dañino si absorbido por la piel.

ADVERTENCIA: ESTE PRODUCTO CONTIENE QUÍMICOS QUE DE ACUERDO CON EL ESTADO DE CALIFORNIA PUEDEN CAUSAR CÁNCER Y DEFECTOS DE NACIMIENTO U OTRO DAÑO REPRODUCTIVO.

Primeros auxilios: Si se traga, NO induzca el vómito. ¡OBTENGA ATENCIÓN MÉDICA INMEDIATA! Llame de inmediato al médico, a la sala de emergencias del hospital o al centro de toxicología. En caso de contacto con los ojos o la piel, enjuague inmediatamente los ojos o piel con abundante agua durante al menos 15 minutos. Busque atención médica. Si experimenta dificultades para respirar, abandone el área y tome aire fresco. Si continúa experimentando dificultades, busque atención médica.

Use sólo con una ventilación adecuada. 63932

MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.
 Reglamentación 443.1 de California SCAQMD: Máx. VOC: 181 g/L; Máx. presión de vapor de VOC incluido: 100 mm Hg; VOC no incluido: 350 mm Hg; Menos de 50% VOC. Reactivo no fotoquímico.

