

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep 08/06/07

SECTION 1

SUNNYSIDE CORPORATION
225 CARPENTER AVENUE
WHEELING, ILLINOIS 60090
EMERGENCY TELEPHONE

(847) 541-5700
(800) 424-9300

FOR INFORMATION:

(847) 541-5700

- SUNNYSIDE CORPORATION
- CHEM TREC

Product Class: Not Applicable
Trade Name: CLEAR WOOD PROTECTANT

Manufacturer's Code:
NPCA HMIS:

725
Health: 1
Flammability: 0
Reactivity: 0

Product Appearance and Odor: Opaque, milky (emulsion) liquid; characteristic, mild odor.

SECTION 2 -- HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

There are no hazardous components per OSHA guidelines.

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

Inhalation: Immediately remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen.

Eye Contact: Immediately flush eyes with plenty of water. Call a physician.

Skin Contact: Immediately wash skin with soap and water. Wash contaminated clothing before reuse.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.

SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range: 212° (F) - I.B.P. Vapor Density: N. A.

Evaporation Rate: N. A.
Weight Per Gallon: 8.32 lbs. % Volatile By Volume: N. A.

Solubility in Water: Disperses readily VOC: <25g/L

SECTION 5 -- FIRE AND EXPLOSION DATA

Flammability Classification:	Not Flammable
Flash Point:	None - Not Flammable
Lower Explosive Limit:	Not Flammable
Extinguishing Media:	Water Spray, Foam, Dry Chemical, CO2
Unusual Fire and Explosion Hazards:	None Known

Special Fire Fighting Procedures: Evacuate personnel to a safe area. Wear self-contained breathing apparatus. Wear full protective equipment.

SECTION 6 -- HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE:	See Section 2
EFFECTS OF OVEREXPOSURE	Eye Contact: Preexisting eye disorder may be aggravated by exposure to this product. Inhalation: Exposure to high vapor concentrations may cause eye and respiratory tract irritation, headache, dizziness, nausea, drowsiness, and loss of consciousness. Skin Contact: Prolonged and repeated contact with skin can cause de-fatting and drying of the skin resulting in skin irritation and dermatitis. Ingestion: Although ingestion is unlikely, liquid would irritate upper digestive tract if swallowed. Carcinogenicity: Components of this product have not been identified as carcinogens by NTP, IARC or OSHA. Chronic Health Hazard: No information available. Acute Health Hazard: No information available.

SECTION 7 -- REACTIVITY DATA

Stability:	Stable
Conditions to Avoid:	Keep container tightly closed. Keep from freezing.
Incompatibility (Materials to Avoid):	Avoid contact with strong oxidizing agents and acids, aluminum at higher temperatures.
Hazardous Decomposition Products:	Combustion may produce CO ₂ , CO, and nitrous oxides.
Hazardous Polymerization:	Will not occur

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Depending on quantity of spill:

1. Add solid absorbent, shovel, or scoop into disposal container and hose or wash down area.
2. Squeegee into pick up container and wash area.

Waste disposal method: Dispose of in accordance with local, state and federal regulations.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection:	Not normally required, however NIOSH approved respirator should be used as needed.
Ventilation:	Not normally required.
Protective Gloves:	Rubber or plastic gloves should be worn.
Eye Protection:	Safety glasses should be worn.
Other Protective Equipment:	Not normally required.
Storage Conditions:	Store in a tightly closed container. Store in a well ventilated area. Keep from freezing. AGITATE CONTENTS OF CONTAINER BEFORE USING.

SECTION 10 -- SPECIAL PRECAUTIONS

Dept. of Labor Storage Category:	Not Applicable
Hygienic Practices:	Prevent eye contact, wash hands after use.
Additional Precautions:	Not Applicable

SECTION 11 -- ADDITIONAL INFORMATION

This product contains the following toxic chemical(s) which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

TOXIC CHEMICAL	CAS #	APPROXIMATE % BY WEIGHT
NONE	NONE	NONE

California Proposition 65: This product contains trace amounts of ethyl acrylate, a chemical known to the state of California to cause cancer.

TRANSPORTATION

U.S. D.O.T. Proper Shipping Name: Not Applicable - Not a D.O.T. Hazard