SUNNYSIDE DECK WASH

TECHNICAL DATA SHEET



SUNNYSIDE DECK WASH

DESCRIPTION

Sunnyside Deck Wash is a combination of cleaning agents designed to clean and remove dirt, mildew, algae and fungus stains. It will restore the appearance of weathered wood, and is also recommended for cleaning composite decks.

ITEM NUMERS & SIZES							
-	<u>Quart</u>	<u>1-Gallon</u> 727G1					
HAZARDOUS INGREDIENTS							
Ingredient Sodium Hypochlorite Sodium Hydroxide		2	<u>CAS#</u> 7681-52-9 1310-73-2		Percent <2.5% 0.2-0.5%		



SAFETY INFORMATION

727

HEALTH:	2
FIRE:	0
REACTIVITY:	1



PRODUCT APPLICATION

Sunnyside Deck Wash should be applied to a dry deck that is free of debris. It should be applied with a plastic pump-up sprayer, taking care to achieve complete coverage while avoiding overspray to adjacent surfaces. The product should be allowed 5-10 minutes to clean the deck, no scrubbing required. Thoroughly rinse the entire surface and surrounding area with large volumes of water to complete the cleansing action.

PHYSICAL PROPERTIES

<u>Typical Properties</u> GRAVITY, (60 °F)	<u>Results</u>
API	
SPECIFIC	1.0306
DENSITY (Lb./GAL)	8.58
DISTILLATION RANGE	209°F.,IBP
FREEZING POINT, °F (°C)	
KAURI BUTANOL (Kb) VALUE	
FLASH POINT, T.C.C. °F	none
FLAMMABLE LIMITS IN AIR, % BY VOLUN	1E
LOWER, AT 100°F (38°C)	
UPPER, AT 200°F (93°C)	
AUTOIGNITION TEMPERATURE, °F (°C)	
COLOR, SAYBOLT	+30
DOCTOR TEST	
CORROSION, 3 HRS. @ 212 °F	
NON-VOLATILES, g/100ml	
ACIDITY	
ALKALINITY (AS NH3, WT%)	
EVAPORATION RATE	
APPEARANCE	Clear, water-white
ODOR	Chlorine odor
VAPOR PRESSURE, mm Hg @ 20 °C	
REFRACTIVE INDEX, @ 20 °C	
SULFUR CONTENT, PPM	
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	
WATER MISCIBILITY	Complete
DOT SHIPPING NAME	Not regulated by U.S. D.O.T.
DOT CLASSIFICATION	as a hazardous material
SHIPPING Wt. at 20 °C	8.58
V.O.C. (g/L)	Not Applicable

These properties are repesentative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

TEST METHOD ASTM Applied

D-1298	:
D-86	
D-1133 D-611 D-56	•
D-1255 D-156 D-484 D-130 D-1353 D-847 D-1614	•
D-1296	•
D-1218 D-1266	
D-1364 D-1722	

See MSDS sheeet for additional Health, Safety, Handling and Regulatory Information available on our website at www.sunnysidecorp.com/msds.html