

ZERO VOC XYLENE/TOLUENE REPLACEMENT

TECHNICAL DATA SHEET

474



SUNNYSIDE ZERO VOC XYLENE/TOLUENE REPLACEMENT

DESCRIPTION

Zero VOC Xylene/Toluene Replacement is used to replace Xylene, Toluene and other volatile organic compounds when a low or zero VOC replacement is required.

ITEM NUMBERS & SIZES

Pint	Quart	1-Gallon	2.5-Gal.	5-Gal.	55-Gal.
	47432	474G1		474G5	

HAZARDOUS INGREDIENTS

Ingredient	CAS#
Acetone	67-64-1
Parachlorobenzo-trifluoride	98-56-6

PHYSICAL PROPERTIES

Typical Properties	Results
GRAVITY, (60 °F)	
API	
SPECIFIC	0.875
DENSITY (Lb./GAL)	7.29
DISTILLATION RANGE @ IBP ° F	133
FREEZING POINT, ° F (° C)	
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT, ° F	
FLASH POINT, T.C.C. ° F	0
FLAMMABLE LIMITS IN AIR, % BY VOLUME	
LOWER, AT 100° F (38° C)	
UPPER, AT 200° F (93° C)	
AUTOIGNITION TEMPERATURE, ° F (° C)	
COLOR (Pt+Co) Max.	5
DOCTOR TEST	
CORROSION, 3 HRS. @ 212 ° F	
NON-VOLATILES, g/100ml	
ACIDITY (as Acetic Acid)	0.002 max.
ALKALINITY (AS NH ₃ , WT%)	0.001 max.
EVAPORATION RATE	Slower than ether
APPEARANCE	Clear, water-white
ODOR	Characteristic, Nonresidual
VAPOR PRESSURE, mm Hg @ 20 ° C	
REFRACTIVE INDEX, @ 20 ° C	
SULFUR CONTENT, PPM	
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	0.5 Max.
WATER MISCIBILITY	Partial
DOT SHIPPING NAME	Acetone solution
DOT CLASSIFICATION	Hazard Class III
SHIPPING Wt. at 20 ° C	7.29
V.O.C. (g/L)	0-Exempt

These properties are representative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

SAFETY INFORMATION

HEALTH:	2
FIRE:	3
REACTIVITY:	0

PRODUCT APPLICATION

Zero VOC Xylene/Toluene Replacement can be used to thin hard to thin oil based coatings, such as porch and deck enamels, anti-rust paints and many other synthetic enamels. Excellent for clean up of brushes and equipment.

TEST METHOD

ASTM	Applied
D-278	
D-1298	■
D-86	■
D-1133	
D-611	
D-56	■
D-1255	
D-156	■
D-484	
D-130	
D-1353	
D-847	
D-1614	
D-1296	■
D-1218	
D-1266	
D-1364	
D-1722	

See MSDS sheet for additional Health, Safety, Handling and Regulatory Information available on our website at www.sunnysidecorp.com/msds.html