VOC COMPLIANT GENERAL PURPOSE THINNER

TECHNICAL DATA SHEET

476



SUNNYSIDE VOC COMPLIANT **GENERAL PURPOSE THINNER**

DESCRIPTION

VOC Compliant General Purpose Thinner is useful as a general purpose clean up solvent and thinner for oil based coatings where a low VOC product is required.

SAFETY INFORMATION

HEALTH: FIRE: REACTIVITY: 3 0

ITEM NUMERS & SIZES

<u>Pint</u> 1-Gallon 2.5-Gal. 5-Gal. 55-Gal. Quart 476G5

476G1 47632

HAZARDOUS INGREDIENTS

Ingredient CAS# 67-64-1 Acetone Aliphatic Naphtha 64742-89-8

PRODUCT APPLICATION

VOC Compliant General Purpose Thinner effectively thins most oil based paints, stains and varnishes. Use for clean up after painting.

PHYSICAL PROPERTIES

Typical Properties	Results
GRAVITY, (60 °F)	
SPECIFIC	0.794
	6.61
DENSITY (Lb./GAL) DISTILLATION RANGEE IBP ° F	133
FREEZING POINT, °F (°C)	133
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT, °F	
FLASH POINT, T.C.C. °F	0
FLAMMABLE LIMITS IN AIR, % BY VOLUME	· ·
LOWER, AT 100°F (38°C)	
UPPER, AT 200°F (93°C)	
AUTOIGNITION TEMPERATURE, °F (°C)	
COLOR (Ptt-Co) Max.	5
DOCTOR TEST	· ·
CORROSION, 3 HRS. @ 212 °F	
NON-VOLATILES, g/100ml	
ACIDITY (as Acetic Acid)	
ALKALINITY (AS NH3, WT%)	
EVAPORATION RATE	Slower than ether
APPEARANCE	Clear, water-white
ODOR	Characteristic, Nonresidual
VAPOR PRESSURE, mm Hg @ 20 °C	
REFRACTIVE INDEX, @ 20 °C	
SULFUR CONTENT, PPM	
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	0.5 Max.
WATER MISCIBILITY	Partial
DOT SHIPPING NAME	Paint related material
DOT CLASSIFICATION	Hazard Class III
SHIPPING Wt. at 20 °C	6.61
V.O.C. (g/L)	23g/L

These properties are repesentative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

TEST METHOD

See MSDS sheeet for additional Health, Safety, Handling and Regulatory Information available on our website at www.sunnysidecorp.com/msds.html