

SUNNYSIDE PHOSPHATE FREE TSP

641



SUNNYSIDE PHOSPHATE FREE TSP

DESCRIPTION

All purpose heavy duty cleaner. Phosphate free, safer for the environment.

ITEM NUMBERS & SIZES

16 oz.	64 oz.
Pouch	Pouch
64116	64164

HAZARDOUS INGREDIENTS

<u>Ingredient</u>	<u>CAS#</u>	<u>Percent</u>
Sodium Meta-Silicate	6834-92-0	80-100%

PHYSICAL PROPERTIES

<u>Typical Properties</u>	<u>Results</u>
GRAVITY, (60 °F)	
API	
SPECIFIC DENSITY (Lb./GAL)	solid
DISTILLATION RANGE	0.88 g/cms
FREEZING POINT, °F (°C)	solid
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT, °F	
FLASH POINT, T.C.C. °F	
FLAMMABLE LIMITS IN AIR, % BY VOLUME	
LOWER, AT 100°F (38°C)	
UPPER, AT 200°F (93°C)	
AUTOIGNITION TEMPERATURE, °F (°C)	
COLOR, SAYBOLT	
DOCTOR TEST	
CORROSION, 3 HRS. @ 212 °F	
NON-VOLATILES, g/100ml	
ACIDITY	
ALKALINITY (AS NH ₃ , WT%)	
EVAPORATION RATE	
APPEARANCE	Clear (in solution)
ODOR	Mild
VAPOR PRESSURE, mm Hg @ 20 °C	
REFRACTIVE INDEX, @ 20 °C	
SULFUR CONTENT, PPM	
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	
WATER MISCIBILITY	Complete
DOT SHIPPING NAME	Disodium trioxosilicate
DOT CLASSIFICATION	
SHIPPING Wt. at 20 °C	
V.O.C. (g/L)	Not Applicable

These properties are representative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

SAFETY INFORMATION

HEALTH: 3
FIRE: 0
REACTIVITY: 0

PRODUCT APPLICATION

Dissolve product in warm water. Use for general cleaning or prior to painting. Rinse thoroughly.

TEST METHOD

<u>ASTM</u>	<u>Applied</u>
D-1298	■
D-86	■
D-1133	
D-611	
D-56	
D-1255	
D-156	
D-484	
D-130	
D-1353	
D-847	
D-1614	
D-1296	■
D-1218	
D-1266	
D-1364	
D-1722	

See MSDS sheet for additional Health, Safety, Handling and Regulatory Information available on our website at www.sunnysidecorp.com/msds.html