

SUNNYSIDE TSP

642



## SUNNYSIDE TSP

**DESCRIPTION**

All Purpose heavy duty cleaner.

**ITEM NUMBERS & SIZES**

<b>16 oz.</b>	<b>64 oz.</b>
<b>Pouch</b>	<b>Pouch</b>
64216	64264

**HAZARDOUS INGREDIENTS**

<u>Ingredient</u>	<u>CAS#</u>	<u>Percent</u>
Trisodium Phosphate	7601-549	80-100%

**PHYSICAL PROPERTIES**

<u>Typical Properties</u>	<u>Results</u>
GRAVITY, (60 °F)	
API	
SPECIFIC DENSITY (Lb./GAL)	solid
DISTILLATION RANGE	0.88 gm/cm <sup>3</sup>
FREEZING POINT, °F (°C)	solid
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT, °F	
FLASH POINT, T.C.C. °F	
FLAMMABLE LIMITS IN AIR, % BY VOLUME	
LOWER, AT 100°F (38°C)	
UPPER, AT 200°F (93°C)	
AUTOIGNITION TEMPERATURE, °F (°C)	
COLOR, SAYBOLT	
DOCTOR TEST	
CORROSION, 3 HRS. @ 212 °F	
NON-VOLATILES, g/100ml	
ACIDITY	
ALKALINITY (AS NH <sub>3</sub> , WT%)	
EVAPORATION RATE	
APPEARANCE	Clear (in solution)
ODOR	Mild
VAPOR PRESSURE, mm Hg @ 20 °C	
REFRACTIVE INDEX, @ 20 °C	
SULFUR CONTENT, PPM	
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	
WATER MISCIBILITY	Complete
DOT SHIPPING NAME	Not regulated as a hazardous material.
DOT CLASSIFICATION	
SHIPPING Wt. at 20 °C	
V.O.C. (g/L)	Not Applicable

These properties are representative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

**SAFETY INFORMATION**

**HEALTH:** 3  
**FIRE:** 0  
**REACTIVITY:** 0

**PRODUCT APPLICATION**

Dissolve product in warm water. Use for general purpose cleaning prior to painting. Rinse thoroughly..

**TEST METHOD**

<u>ASTM</u>	<u>Applied</u>
D-1298	■
D-86	■
D-1133	
D-611	
D-56	
D-1255	
D-156	
D-484	
D-130	
D-1353	
D-847	
D-1614	
D-1296	■
D-1218	
D-1266	
D-1364	
D-1722	

See MSDS sheet for additional Health, Safety, Handling and Regulatory Information available on our website at [www.sunnysidecorp.com/msds.html](http://www.sunnysidecorp.com/msds.html)