GLOSS REMOVER TECHNICAL DATA SHEET 722



# SUNNYSIDE GLOSS REMOVER

SAFETY INFORMATION

2

HEALTH: FIRE: REACTIVITY:

#### DESCRIPTION

Sunnyside Gloss Remover cleans, deglosses and degreases most surfaces, leaving them ready for painting. Prepares latex or oil base paint surfaces without sanding.

## ITEM NUMERS & SIZES

 Pint
 Quart
 1-Gallon
 2.5-Gal.
 5-Gal.
 55-Gal.

 72232
 722G1
 5-Gal.
 5-Gal.
 5-Gal.

#### HAZARDOUS INGREDIENTS

IngredientCAS#PercentMineral Spirits64742-88-7

Dipropylene Glycol

 Methyl Ether
 34590-94-8

 n-Methyl 2-Pyrolidone
 872-50-4

# PRODUCT APPLICATION

Apply to area no larger than 8 ft. by 10 ft., using fine or extra fine steelwool as an applicator. Use only enough pressure to etch surface slightly. Wipe deglossed area with a lint-free rag or paper towels to remove any remaining steelwool dust. Allow 1 to 2 hours before repainting deglossed surfaces.

# PHYSICAL PROPERTIES

Typical Properties GRAVITY, (60 °F)	Results
API	52.5
SPECIFIC	0.769
DENSITY (Lb./GAL)	6.4
DISTILLATION RANGEE.° F.	354 (IBP)
FREEZING POINT, °F (°C)	354 (IBI )
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT. °F	
FLASH POINT, T.C.C. °F	
FLAMMABLE LIMITS IN AIR. % BY VOLUME	
LOWER, AT 100°F (38°C)	N.E.
UPPER, AT 200°F (93°C)	N.E.
AUTOIGNITION TEMPERATURE, °F (°C)	N.E.
COLOR. SAYBOLT	N.⊑. +30
DOCTOR TEST	+30
CORROSION, 3 HRS. @ 212 °F	
NON-VOLATILES, q/100ml	
ACIDITY	NEUTRAL
ALKALINITY (AS NH3, WT%)	NEUTRAL
EVAPORATION RATE	Slower than ether
APPEARANCE	
ODOR	Clear, water-white Mixed Solvent
	N.E.
VAPOR PRESSURE, mm Hg @ 20 °C	N.E.
REFRACTIVE INDEX, @ 20 °C	10
SULFUR CONTENT, PPM	<2
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	AL P. 9.1
WATER MISCIBILITY	Negligible
DOT SHIPPING NAME	Not Hazardous
DOT CLASSIFICATION	Combustible Liquid - Class II.
SHIPPING Wt. at 20 °C	6.4
V.O.C. (g/L)	768

These properties are repesentative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

## TEST METHOD

ASTM	Applied
D-278 D-1298	:
D-86	_
D-1133 D-611 D-56	
D-1255 D-156 D-484 D-130 D-1353 D-847 D-1614	:
D-1296	•
D-1218 D-1266	•
D-1364 D-1722	

See MSDS sheeet for additional Health, Safety, Handling and Regulatory Information available on our website at www.sunnysidecorp.com/msds.html