

## SUNNYSIDE CLEAR WOOD PROTECTANT

725



## SUNNYSIDE CLEAR WOOD PROTECTANT

**DESCRIPTION**

Sunnyside Clear Formula Exterior Wood Protectant is a silicon waterproofer that dries to a clear, penetrating coating.

**ITEM NUMERS & SIZES**

Quart	1-Gallon	5-Gallon
72532	725G1	725G5

**HAZARDOUS INGREDIENTS**

Ingredient	CAS#	Percent
No hazardous components by OSHA definition.		

**PHYSICAL PROPERTIES**

Typical Properties	Results
GRAVITY, (60 °F)	
API	
SPECIFIC DENSITY (Lb./GAL)	0.9993
DENSITY (Lb./GAL)	8.32
DISTILLATION RANGE	212°F.IBP
FREEZING POINT, °F (°C)	
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT, °F	
FLASH POINT, T.C.C. °F	
FLAMMABLE LIMITS IN AIR, % BY VOLUME	
LOWER, AT 100°F (38°C)	
UPPER, AT 200°F (93°C)	
AUTOIGNITION TEMPERATURE, °F (°C)	
COLOR, SAYBOLT	
DOCTOR TEST	
CORROSION, 3 HRS. @ 212 °F	
NON-VOLATILES, g/100ml	
ACIDITY	
ALKALINITY (AS NH <sub>3</sub> , WT%)	
EVAPORATION RATE	
APPEARANCE	Milky White
ODOR	Mild
VAPOR PRESSURE, mm Hg @ 20 °C	
REFRACTIVE INDEX, @ 20 °C	
SULFUR CONTENT, PPM	
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	
WATER MISCIBILITY	Complete
DOT SHIPPING NAME	Not regulated by US DOT as a hazardous material.
DOT CLASSIFICATION	
SHIPPING Wt. at 20 °C	8.32
V.O.C. (g/L)	20grams/L.

These properties are representative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

**SAFETY INFORMATION**

**HEALTH:** 1  
**FIRE:** 0  
**REACTIVITY:** 0

**PRODUCT APPLICATION**

Sunnyside Clear Wood Protectant protects and waterproofs a variety of exterior wood surfaces. It penetrates and locks into the wood, providing protection from the inside, unlike inferior surface treatments.

**TEST METHOD**

ASTM	Applied
D-1298	■
D-86	■
D-1133	
D-611	
D-56	
D-1255	
D-156	
D-484	
D-130	
D-1353	
D-847	
D-1614	
D-1296	■
D-1218	
D-1266	
D-1364	
D-1722	

See MSDS sheet for additional Health, Safety, Handling and Regulatory Information available on our website at [www.sunnysidecorp.com/msds.html](http://www.sunnysidecorp.com/msds.html)