ISOPROPYL ALCOHOL TECHNICAL DATA SHEET 832



# SUNNYSIDE ISOPROPYL ALCOHOL

S

0

sunnyside isopropyll alcohol 99%

# DESCRIPTION

Sunnyside Isopropyl Alcohol (Anhydrous) is a flammable, fast evaporating, colorless solvent with a characteristic odor. It is an excellent latent solvent for many resins used in the coatings industry. Meets Federal specification TT-1-735A grade A&B, and ASTM specification D 770.

### ITEM NUMERS & SIZES

 
 Pint
 Quart
 1-Gallon 832G1
 2.5-Gal. 832G5
 5-Gal. 832G5
 55-Gal. 832G5

#### HAZARDOUS INGREDIENTS

 Ingredient
 CAS#
 Percent

 Isopropyl Alcohol
 67-63-0
 99.9%

#### PRODUCT IMAGE

# SAFETY INFORMATION

2

3

0



## ONE GALLON ■ 3.785 LITERS

PRODUCT APPLICATION

Isopropyl Alcohol has numerous cleaning and solvent industrial applications. It is completely water soluble, and has a familiar, clean odor

# PHYSICAL PROPERTIES

Typical Properties	<u>Results</u>
GRAVITY, (60 °F) API	
SPECIFIC	0.786
DENSITY (Lb./GAL)	6.54
DISTILLATION RANGEE IBP ° F	178
FREEZING POINT, °F (°C)	-127
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT. °F	
FLASH POINT, T.C.C. °F	55
FLAMMABLE LIMITS IN AIR, % BY VOLUME	
LOWER, AT 100°F (38°C)	2.3
UPPER, AT 200°F (93°C)	12.75
AUTOIGNITION TEMPERATURE, °F (°C)	680
COLOR (Ptt-Co) Max.	10
DOCTOR TEST	
CORROSION, 3 HRS. @ 212 °F	
NON-VOLATILES, g/100ml	
ACIDITY (as Acetic Acid)	
ALKALINITY (AS NH3, WT%)	0
EVAPORATION RATE	Slower than ether
APPEARANCE	Clear, water-white
ODOR VAPOR PRESSURE, mm Hg @ 20 °C	Characteristic, Nonresidual 32.8
REFRACTIVE INDEX, @ 20 °C	1.3776
SULFUR CONTENT, PPM	1.5770
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	
WATER MISCIBILITY	Complete
DOT SHIPPING NAME	Isopropanol
DOT CLASSIFICATION	Hazard Class III
SHIPPING Wt. at 20 °C	6.54
V.O.C. (g/L)	789

These properties are repesentative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

# TEST METHOD

	ASTM	Applied
	D-278 D-1298	:
I	D-86	•
	D-1133 D-611 D-56	•
   	D-1255 D-156 D-484 D-130 D-1353 D-847	:
	D-847 D-1614	•
I	D-1296	:
	D-1218 D-1266	-
	D-1364 D-1722	

See MSDS sheeet for additional Health, Safety, Handling and Regulatory Information available on our website at www.sunnysidecorp.com/msds.html