

LACQUER
RETARDER



sunnyside
lacquer
retarder

California
SCAQMD Rule 443.1
Max. VOC: 864 g/L
Max Vapor Pressure
of VOC: 83 mm Hg
Non-Photochemically Reactive

LACQUER
RETARDER



Specially formulated.

for
use with
the finest
lacquers &
epoxies

DANGER!

HARMFUL OR FATAL IF SWALLOWED. FLAMMABLE LIQUID & VAPOR.
VAPOR HARMFUL. VAPORS MAY CAUSE FLASH FIRE. SKIN AND EYE IRRITANT.
MAY BE HARMFUL IF ABSORBED THROUGH SKIN.
Carefully read all cautions elsewhere on this container.

ONE GALLON ■ 3.785 LITERS

Sunnyside Lacquer Retarder is designed to slow the evaporation rate of lacquers and epoxies. Intended primarily for use with nitrocellulose lacquers, this product will also help prevent blushing when lacquers are applied in high humidity conditions. Do not exceed amounts of thinners and / or retarders recommended by lacquer manufacturer.

Safety Note: Lacquers and epoxies give off flammable vapors during drying. Always follow the coating manufacturer's directions and warnings, and be aware of the increased fire hazard when coating larger areas. If ventilation equipment is used, it must be explosion proof. If lacquer retarder is used for any other purpose, limit flammable vapors by using only a few ounces at a time. Wait until all vapors are gone between uses. Read all cautions on this label prior to using.

CAUTIONS: CONTAINS N-BUTYL ACETATE, N-BUTYL ALCOHOL, ETHYLENE GLYCOL MONOBUTYL ETHER, XYLENE. Keep away from heat, sparks and flame. Vapors are heavier than air and may travel long distances to other rooms or lower areas. DO NOT use in confined areas such as basements or bathrooms. Open all doors and windows to provide plenty of fresh air cross ventilation equal to outdoor conditions. DO NOT smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may linger for 30 minutes or more after use. If you smell Lacquer Retarder, vapors are still present. Do not turn ignition sources on or relight pilot lights until certain that all vapors are gone. Avoid rubbing, friction may cause static electric sparks which may ignite vapors. Do not attempt to start or re-ignite charcoal, wood or any other fire with this product. An explosive fire may result or fire may flash back into the can and explode. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency. Do not transfer to unlabeled containers.

Health Hazards: Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Avoid breathing vapor or spray mist. If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area to obtain fresh air. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

First Aid: : If swallowed, DO NOT induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water for at least 15 minutes. Get medical attention. For skin contact, wash thoroughly for at least 15 minutes. Get medical attention if irritation persists. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention.

**Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.**

SUNNYSIDE CORPORATION
Consumer Products Division
Wheeling, IL 60090-6095

For more information
contact us at 1-800-323-8611
or visit us on the web at
www.sunnysidecorp.com.



© 2006 S.C.