

### PRECAUTIONARY STATEMENTS:

**Obtain special instructions before use.** Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/ lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors/spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use media other than water to extinguish. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

**Suitable extinguishing media:** Dry powder, Foam, Carbon dioxide.

**First aid measures:** If exposed or concerned: Get medical advice/attention.

**Inhalation:** Remove person to fresh air and keep comfortable for breathing. Call a doctor.

**Skin contact:** Rinse skin with water/shower. Remove/take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.

**Eye contact:** Rinse eyes with water as a precaution for at least 15 minutes. Get medical attention.

**Ingestion:** Rinse mouth. Do not induce vomiting. Call a poison center/doctor/physician.

### ADDITIONAL INFORMATION:

#### Precautions for safe handling:

Flammable vapors may accumulate in the container. Wear personal protective equipment. Take all necessary technical measures to avoid or minimize the release of the product in the workplace. Limit quantities of product to the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing.

# PRO SOLUTIONS™

For the Automotive Professional

## 560 URETHANE REDUCER

■ Fast Dry  
60 Degree



### DANGER!

**HAZARD STATEMENTS:** Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life.

**FIVE GALLONS 18.925 LITERS**

PAINT RELATED MATERIAL  
**UN1263**

**RED LABEL  
REQUIRED**

**Contains:** Acetone, Toluene, Xylene, Methyl Isobutyl Ketone and N-Butyl Acetate.

**WARNING:** This product contains chemicals known to the state of California to cause cancer and birth defects, or other reproductive harm.

**FOR PROFESSIONAL USE ONLY.  
KEEP OUT OF REACH OF CHILDREN.**



#### WARNING!

When empty, hazardous liquid and/or vapor may remain in this container and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose to heat, sparks, flame or other sources of ignition. It may explode. Do not reuse empty container. Dispose of properly.

**In case of fire:** Use foam, CO2 or dry chemical. Do not use direct water stream, it will spread fire.

**In case of spills or leaks:** SMALL SPILLS: Soak up with absorbent material. LARGE SPILLS: Dike and pump into drums. Prevent material from entering drains, sewers or waterways.

**Chemical emergency:** Spill, Leak, Exposure or Accident, CALL-CHEMTREC evenings or weekends 800-424-9300. During normal business hours (847) 541-5700.

Use gloves and eye protection when handling. Ground container when transferring contents.

#### HAZARD RATINGS/CLASIFICACIONES DE RIESGOS:

HEALTH/SALUD	2
FLAMMABILITY/INFLAMABILIDAD	3
REACTIVITY/REACTIVIDAD	1

#### ¡ADVERTENCIA!

Al vaciar este envase, puede quedar líquido o vapor peligroso al interior del mismo, lo cual puede ocasionar riesgos. No aplique presión ni corte, suelde de ninguna manera, perfore, esmerile, ni exponga a fuentes de calor, chispas, llama u otras fuentes de encendido. Este envase puede explotar. No vuelva a usar el envase vacío. Devuelva los envases vacíos a su proveedor para que sea reacondicionado profesionalmente para asegurar su seguridad; otros envases deben ser desechados adecuadamente.

**En caso de incendio:** Use espuma, CO2 o químicos secos. No use un chorro directo de agua; esto causará que la llama se expanda.

**En caso de derrames o pérdidas:** DERRAMES PEQUEÑOS: Recoger con material absorbente. DERRAMES GRANDES: Contener y bombear en tambores. Evite que el material ingrese a los drenajes, cañerías o corrientes de agua.

**Emergencia de carácter químico:** Derrame, pérdida, exposición o accidente: LLAME A CHEMTREC en la tarde o fines de semana al: (800) 424-9300. Durante el horario de trabajo (800) 323-8611.

Cuando lo maneje, use guantes y protección para los ojos. Aplique una conexión a tierra cuando transvasa el contenido.

Product code: 560G5P



**SUNNYSIDE CORPORATION**  
Wheeling, IL 60090-6095

For more information contact us at 1-800-323-8611  
or visit us on the web at [www.sunnysidecorp.com](http://www.sunnysidecorp.com).  
© 2017 S.C.

