

SUNNYSIDE QUALITY PRODUCTS SINCE 1893

BACK TO NATURE

HI-SPEED READY-STRIP™

CITRUS PAINT & VARNISH REMOVER

FASTER

Removes paint or varnish in about 1/2 hour
Strips 3 layers in one application

SAFER

New water-based technology
No methylene chloride & non-flammable



LOW ODOR • ENVIRONMENTALLY SAFE

CAUTION! EYE AND SKIN IRRITANT.
HARMFUL IF SWALLOWED. Read other cautions
elsewhere on container. Use only as directed.

Removedor de pintura y barniz cítrico

PRECAUCIÓN! IRRITA LOS OJOS Y LA PIEL.
DANINO SI SE INGIERE. Lea las otras advertencias
que aparecen en el envase.

ONE HALF GALLON (1.9L)

Description: Hi-Speed Ready-Strip™ is a convenient way of removing paint or varnish. It features a "no-drip" formula and the ability to stay wet longer. The special blend of chemicals eliminates methylene chloride, caustic, or other harsh stripping chemicals. It removes most varieties of paints, varnishes, latex, alkyds, stains, enamels, lacquers, and polyurethanes. It works on interior and exterior surfaces including wood, plaster, metal, brick, masonry, concrete, marble, veneers, etc. Hi-Speed Ready-Strip is not to be used on sheetrock, plastic, rubber or linoleum surfaces.

DO A TEST AREA FIRST TO DETERMINE RESULTS. SHAKE BOTTLE BEFORE USE.

Directions: Mask any areas not being stripped with plastic and masking tape. Apply at temperatures between 60° and 80° F. Apply Hi-Speed Ready-Strip liberally with a brush, 1/2" nap roller cover or putty knife to the surface to be stripped. **Application of product should be heavy; spreading product too thin will not achieve desired results.** Depending upon the type and amount of paint, the remover can work in as little as 30 minutes, or stay wet and active for up to 4 hours or more. Periodically test scrape a small area to determine if the paint or varnish is ready to be removed. Use a stiff putty knife to lift paint from flat surfaces or a stiff bristle brush for detailed areas. After initial lifting, use a nylon brush or stripping pad with Ready-Strip Wash or light amounts of water for final clean-up of residue. Clean up with water. Surface should be dry before repainting.

CAUTION: CONTAINS DIBASIC ESTERS, BENZYL ALCOHOL AND FORMIC ACID. Do not transfer to unlabeled containers. May cause eye and skin irritation on contact.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

SAFETY & FIRST AID: Rubber gloves and safety glasses are recommended for eye and skin protection. Avoid eye contact. If eye contact occurs, immediately flush with plenty of water for 15 minutes. Avoid prolonged and repeated contact with skin. If skin contact occurs, wash with soap and water. Do not take internally. If swallowed do not induce vomiting. Give 1 or 2 glasses of water and call a physician immediately. Provide adequate ventilation in confined areas.

KEEP OUT OF REACH OF CHILDREN.

California SCAQMD Rule 443.1: Max. VOC 391 g/L; Max Vapor Pressure of VOC: 28.5 mm Hg.
Non-photochemically Reactive. Less than 50% VOC.

For questions or comments about this product,
call 1-800-323-8611 or visit us on the web at
www.sunnysidecorp.com

 **SUNNYSIDE CORPORATION**
Consumer Products Division
Wheeling, IL 60090-6095 © 5/2010 S.C.

Product #68564

