SUNNYSIDE QUALITY PRODUCTS SINCE 1893



NEUTRALIZER

LIFT-N-STRIP NEUTRALIZER SOLUTION IS USED TO NEUTRALIZE THE RESIDUE REMAINING ON SURFACES AFTER THE APPLICATION OF LIFT-N-STRIP PAINT REMOVER



CAUTION! VAPOR HARMFUL. EYE & SKIN IRRITANT. COMBUSTIBLE LIQUID & VAPOR. Carefully read all other warnings and directions elsewhere on label. Use only as directed.

1 GALLON (3.8L)

INSTRUCTIONS FOR USE:

- **1.** Clean off as much residue of removed paint and remover from the surface as possible. Wash off remaining residue using a bristle brush (best for detailed areas), or sponge or spray off residue with sprayer (keeping pressure low on woodwork).
- 2. Spray Lift-N-Strip Neutralizer on to the stripped surface. Work neutralizer into surface using brush or pad if necessary. Leave on for twenty-four hours. Wash off with clean water. Apply another coating of neutralizer and leave on for six hours. Rinse surface with steady stream of clear water. Allow it to dry. If a white powder appears, dry brush off powder and if it reappears, surface needs to be re-neutralized.

3. INSURE THAT SURFACE IS THOROUGHLY DRY BEFORE RECOATING.

4. Take a pH reading of the surface. If dry surface shows a pH over 8, surface should be re-neutralized and a new pH level should be taken.

CAUTION: CONTAINS ACETIC ACID. Keep away from heat and flame. Avoid breathing vapors or spray mist. Do not transfer to unlabeled containers. May cause eye and skin irritation on contact. Close container after use.

SAFETY & FIRST AID: Rubber gloves and safety glasses are recommended for eye and skin protection. Avoid eye contact. If eye contact occurs, immediately flush with plenty of water for 15 minutes. Avoid prolonged and repeated contact with skin. If skin contact occurs, wash with soap and water. Do not take internally. If swallowed do not induce vomiting. IN ALL CASES GET MEDICAL ATTENTION IMMEDIATELY.

Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN.

SUNNYSIDE CORPORATION

Consumer Products Division Wheeling, IL 60090-6095



For more information contact us at 1-800-323-8611 or visit us on the web at www.sunnysidecorp.com.

© 5/2010 S C

Product #675G1

