

SUNNYSIDE QUALITY PRODUCTS SINCE 1893



BACK TO NATURE

READY-STRIP™



NON-FLAMMABLE
WATER CLEAN-UP

HEAVY-DUTY ADHESIVE REMOVER

- Removes Adhesives, Mastics and Contact Cement
- Use on Wood, Concrete, Brick, Stone, Marble, and Metal
- Safer to Use — Contains no Methylene Chloride or Caustics

Read other cautions elsewhere on container. Use only as directed.

ONE HALF GALLON (1.9L)

CAUTION! EYE AND SKIN IRRITANT.

- READY-STRIP ADHESIVE REMOVER™ will safely remove most mastics and adhesives in a single application.
- Stays wet for extended periods of time to penetrate and lift heavy builds.
- User Friendly • Odorless • Heavy Duty • Non-Flammable • Safer to Use • Easily Cleaned-Up with Water
- Contains NO Methylene Chloride or caustics.
- No drip formula clings to vertical surfaces and completely fills detailed areas.
- Use on interior or exterior surfaces including wood, plaster, concrete, brick, stone, masonry, marble, metal and veneers (DO NOT use on sheetrock, plastic, rubber or linoleum surfaces)
- Works on most Construction Adhesives, Flooring Adhesives, and Contact Cement.
- Stir only. **DO NOT SHAKE.**

DO A TEST AREA FIRST TO DETERMINE RESULTS.

Directions: Mask any areas not being removed with plastic and masking tape. For best results apply at temperatures between 60°F and 80°F. Apply READY-STRIP™ ADHESIVE REMOVER liberally to the surface with a brush, 1/2" nap paint roller, putty knife, or squeegee so that the remover completely covers the color of the surface to be stripped (20 mils thick). **Do not brush out too thin like a coat of paint.** It covers approximately 35-50 sq. ft. per half gallon. Check applied area at 2-4 hours, then periodically thereafter. As a rule of thumb, the thicker the mastic, the longer the product should be left on. The remover will usually remove most mastics and adhesives within 6-8 hours. Heavier builds may take longer (12-24+ hours). Use a stiff putty knife or floor scraper to lift the mastic or adhesive. After initial lifting, use a nylon brush or stripping pad with READY-STRIP™ Wash or light amounts of water to remove any residue. Final clean-up should be done with water. No need to neutralize (acid wash) surface. Surface should be completely dry before application of new mastic or adhesive. Clean tools promptly after use with soap and water.

Hints: Let the READY-STRIP ADHESIVE REMOVER do the work. Give it the proper time to penetrate the adhesive layers or its purpose is defeated. Mist the area to be removed with water prior to removal may make lifting of the coating easier. If desired results are not achieved at first, leave remover on longer if still wet, or apply a thicker coat. If still tacky and moist, reapply remover over itself. If completely dry, scrape off and reapply. Product activity is reduced below a temp. of 60°F and may require additional dwell time before all layers of adhesive are removed.

CAUTION: CONTAINS N-METHYL-2-PYRROLIDONE, DIBASIC ESTERS, AND FORMIC ACID. Do not transfer to unlabeled containers. May cause eye and skin irritation on contact. Close container after use.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

SAFETY & FIRST AID: Rubber gloves and safety glasses are recommended for eye and skin protection. Avoid eye contact. If eye contact occurs, immediately flush with plenty of water for 15 minutes. Avoid prolonged and repeated contact with skin. If skin contact occurs, wash with soap and water. Do not take internally. If swallowed do not induce vomiting. Give 1 or 2 glasses of water and call a physician immediately. Provide adequate ventilation in confined areas or use NIOSH approved respirator.

KEEP OUT OF REACH OF CHILDREN.

California SCAQMD Rule 443.1 Max. VOC 226 g/L; Max Vapor Pressure of VOC: 28.5 mm Hg. Non-photochemically Reactive. Less than 20% VOC.

LIMITED WARRANTY: This product is warranted such that it will be free from defects in material or workmanship and purchasers sole remedy is replacement of defective product. This warranty is made in lieu of any other warranties, expressed or implied, including warranties of merchantability or fitness. Company shall not be liable for any loss, damage, or injury, direct, consequential, or incidental from use of product. The purchaser shall be responsible for determining suitability of the product for his/her intended use.

For questions or comments about this product, call 1-800-323-8611 or visit us at www.sunnysidecorp.com



SUNNYSIDE CORPORATION
Consumer Products Division
Wheeling, IL 60090-6095
©4/2016 S.C.

Product #67864

