

## DANGER!

### Hazard statement

Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

### Precautionary statement

#### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/eye protection/face protection.

#### Response

If swallowed: Do NOT induce vomiting. Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Use appropriate media to extinguish. Collect spillage.

#### Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

**WARNING:** THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

### Supplemental information

Usage: Keep container tightly closed. Closures must be retained and tight for returning. Flammables and Combustibles: Ground and bond to certified grounding system, and use spark proof tools.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.



sunnyside

# MINERAL SPIRITS

## MFG# 80355



**Precautions:** Keep away from heat, sparks and flame. Do not take internally. Avoid contact with eyes or skin. Do not breathe vapor or spray mist. Do not transfer contents to unlabeled containers. Keep container closed when not in use.

USE ONLY WITH ADEQUATE VENTILATION.  
KEEP OUT OF REACH OF CHILDREN.


**Personal Protection:** Vapor concentrations should be kept at safe levels. See Safety Data Sheet for occupational exposure limits. If splashing or skin contact is possible, use appropriate protective gear, such as goggles, aprons, boots, etc. The use of rubber or neoprene gloves is recommended.

#### Health Hazards:

##### POSSIBLE HEALTH EFFECTS OF OVEREXPOSURE

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. This is sometimes referred to as "painter's syndrome." Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Prolonged or repeated skin contact may cause drying, cracking and irritation of the skin, resulting in possible dermatitis. Dizziness and headache are signs of overexposure. Under extreme conditions overexposure may result in loss of consciousness.

**SEE SAFETY DATA SHEET FOR ADDITIONAL INFORMATION.**



#### WARNING

When empty, hazardous liquid and/or vapor may remain in the container and can be dangerous. Do not pressurize, cut, braze, solder, drill, grind or expose to heat, sparks, flame or others sources of ignition. It may explode. Dispose of properly.

**In case of fire:** Use foam, CO<sup>2</sup> or dry chemical. Do not use direct water, steam, it will spread fire.

**In case of spills or leaks:** SMALL SPILLS: Soak up with absorbent material. LARGE SPILLS: Dike and pump into drums. Prevent material from entering drains, sewers water ways.

**Chemical emergency:** Spill, Leak, Exposure or Accident, CALL CHEMTREC evenings or weekends 800-424-9300. During normal business hours (847) 541-5700.

**This product for industrial use ONLY:** Use gloves and eye protection when handling. Ground container when transferring contents.

#### HAZARD RATINGS/ CLASIFICACIONES DE RIESGOS:

HEALTH/SALUD	2
FLAMMABILITY/INFLAMABILIDAD	3
REACTIVITY/REACTIVIDAD	0

#### ¡ADVERTENCIA!

Al vaciar este envase, puede quedar líquido o vapor peligroso al interior del mismo, lo cual puede ocasionar riesgos. No aplique presión ni corte, suelde de ninguna manera, perfore, esmerile, ni exponga a fuentes de calor, chispas, llama u otras fuentes de encendido. Este envase puede explotar. No vuelva a usar el envase vacío. Devuelva los envases vacíos a su proveedor para que sea reacondicionado profesionalmente para asegurar su seguridad; otros envases deben ser desechados adecuadamente.

**En caso de incendio:** Use espuma, CO<sub>2</sub> o químicos secos. No use un chorro directo de agua; esto causará que la llama se expanda. En caso de derrames o pérdidas:

**DERRAMES PEQUEÑOS:** Recoger con material absorbente. DERRAMES GRANDES:

Contener y bombear en tambores. Evite que el material ingrese a los drenajes, cañerías o corrientes de agua.

**Emergencia de carácter químico:** Derrame, pérdida, exposición o accidente: LLAME A CHEMTREC en la tarde o fines de semana al: (800) 424-9300. Durante el horario de trabajo (800) 323-8611.

**Este producto es entendido SOLAMENTE para uso industrial:** Cuando lo maneje, use guantes y protección para los ojos. Aplique una conexión a tierra cuando transvasa el contenido.

**Contains: 55 gallons**

For more information contact us at 1-800-323-8611 or visit us on the web at [www.sunnysidecorp.com](http://www.sunnysidecorp.com).

© 2015 SUNNYSIDE CORPORATION  
WHEELING, IL 60090-6095

