

## DANGER!

### Hazard statement

Flammable liquid and vapor. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. Suspected of causing cancer. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

### Precautionary statement

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear eye protection/face protection. Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

If swallowed: Do not induce vomiting. Immediately call a poison control center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

#### Storage

Store in a well-ventilated place. Keep cool. Store locked up.

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

**WARNING:** THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

### Supplemental information

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion. 1% of the mixture consists of component(s) of unknown acute inhalation toxicity. This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Usage: Keep container tightly closed. Closures must be retained and tight for returning. Flammables and Combustibles: Ground and bond to certified grounding system, and use spark proof tools.

  
sunnyside

**XYLOL**  
**(XYLENE)**  
**MFG# 82255**



**CAUTIONS:** CONTAINS XYLENE AND ETHYLBENZENE. Keep away from heat, sparks and flame. Vapors are given off rapidly during use and may ignite explosively. Vapors are heavier than air and may travel long distances to other rooms or lower areas. DO NOT use in confined areas. Use only in area well ventilated by moving air. Keep a constant flow of fresh air until all vapors (odors) are gone. If ventilation equipment is used it must be explosion proof. DO NOT smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not turn ignition sources on or relight pilot lights until certain that all vapors are gone. Avoid rubbing; friction may cause static electric sparks which may ignite vapors.

**Safety Note:** Paints thinned with Xylol give off flammable vapors during drying. Always follow the coating manufacturer's directions and warnings, and be aware of the increased fire hazard when coating larger areas.

**Health Hazards.** Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Avoid breathing vapor or spray mist.

If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area to obtain fresh air. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

**Cancer Information:** This product contains Ethylbenzene. The International Agency for Research on cancer has evaluated Ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans.

**SEE SAFETY DATA SHEET FOR ADDITIONAL INFORMATION.**

RQ Xylenes,

RED LABEL  
REQUIRED

**UN 1307**



#### WARNING

When empty, hazardous liquid and/or vapor may remain in the container and can be dangerous. Do not pressurize, cut, braze, solder, drill, grind or expose to heat, sparks, flame or others sources of ignition. It may explode. Dispose of properly.

**In case of fire:** Use foam, CO<sup>2</sup> or dry chemical. Do not use direct water, steam, it will spread fire.

**In case of spills or leaks:** SMALL SPILLS: Soak up with absorbent material. LARGE SPILLS: Dike and pump into drums. Prevent material from entering drains, sewers water ways.

**Chemical emergency:** Spill, Leak, Exposure or Accident, CALL CHEMTREC evenings or weekends 800-424-9300. During normal business hours (847) 541-5700.

**This product for industrial use ONLY:** Use gloves and eye protection when handling. Ground container when transferring contents.

#### HAZARD RATINGS/ CLASIFICACIONES DE RIESGOS:

HEALTH/SALUD	2
FLAMMABILITY/INFLAMABILIDAD	3
REACTIVITY/REACTIVIDAD	0

#### ¡ADVERTENCIA!

Al vaciar este envase, puede quedar líquido o vapor peligroso al interior del mismo, lo cual puede ocasionar riesgos. No aplique presión ni corte, sude de ninguna manera, perfore, esmerile, ni exponga a fuentes de calor, chispas, llama u otras fuentes de encendido. Este envase puede explotar. No vuelva a usar el envase vacío. Devuelva los envases vacíos a su proveedor para que sea reacondicionado profesionalmente para asegurar su seguridad; otros envases deben ser desechados adecuadamente.

**En caso de incendio:** Use espuma, CO<sub>2</sub> o químicos secos. No use un chorro directo de agua; esto causará que la llama se expanda. En caso de derrames o pérdidas:

**DERRAMES PEQUEÑOS:** Recoger con material absorbente. DERRAMES GRANDES:

Contener y bombear en tambores. Evite que el material ingrese a los drenajes, cañerías o corrientes de agua.

**Emergencia de carácter químico:** Derrame, pérdida, exposición o accidente: LLAME A CHEMTREC en la tarde o fines de semana al: (800) 424-9300. Durante el horario de trabajo (800) 323-8611.

**Este producto es entendido SOLAMENTE para uso industrial:** Cuando lo maneje, use guantes y protección para los ojos. Aplique una conexión a tierra cuando transvasa el contenido.

**Contains: 55 gallons**

Phone: 1-800-323-8611 or visit us on the web at  
www.sunnysidecorp.com.  
© 2015 SUNNYSIDE CORPORATION  
WHEELING, IL 60090-6095



0 76542 00177 5