

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U. S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List) CLEAN-N-DIP CONCENTRATE	<i>Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</i>
--	--

Section I

Manufacturer's Name Sunnyside Corporation	Manufacturer's Code: 655	Emergency Telephone Number Chem Trec (800) 424-9300
Address (Number, Street, City, and ZIP Code) 225 Carpenter Avenue Wheeling, IL 60090		Telephone Number for Information (847) 541-5700
		Date Prepared 09/19/11
		Signature of Preparer (optional)

Section II-Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits	% (optional)
Benzyl Alcohol (100-51-6)		Not Established		40-60%
Non-Hazardous Components		N/A		40-60%

Section III- Physical/Chemical Characteristics

Boiling Point 100 ⁰ C, 212 ⁰ F		Specific Gravity (H₂O=1) 1.01	
Vapor Pressure (mm Hg.) 13mm Hg at 25 ⁰ C		Melting Point N/A	
Vapor Density (AIR =1) 8.6-8.7		Evaporation Rate (Butyl Acetate=1) <1.	
Solubility in Water Considerable			
Appearance and Odor Milky white, faint aromatic odor			

Section IV- Fire and Explosion Hazard Data

Flash Point (Method Used) over 200 ⁰ F	Flammable Limits	LEL N/A	UEL N/A
Extinguishing Media Use CO ₂ , foam, or dry chemical to extinguish fire.			
Special Fire Fighting Procedures. Wear self-contained, positive pressure breathing apparatus and full firefighting protective clothing.			
Hazard Rating for Flammability 1			
Unusual Fire and Explosion Hazards Decomposition under fire conditions will generate carbon monoxide and may generate other toxic vapors.			
N/A = Not Applicable			

Section V-Reactivity Data

Stability	Unstable		Conditions to Avoid Hot or cold Storage
	Stable	X	REACTIVITY = 0
Incompatibility (Materials to Avoid)		Strong oxidizers, acids and alkalies	
Hazardous Decomposition or Byproducts		Thermal decomposition (combustion) will produce carbon monoxide and dioxide.	
Hazardous Polymerization	May Occur		Conditions to Avoid N/A
	Will Not Occur	X	

Section VI-Health Hazard Data

Route(s) of Entry:	Inhalation	Skin	Ingestion
	1	1	1
Health Hazards (Acute and Chronic) Direct contact or exposure to mists and vapor may cause slight to moderate eye irritation. Prolonged or repeated exposure to product, vapors, or mists may cause slight skin irritation. Ingestion may cause moderate to severe irritation of the gastrointestinal tract. Inhalation exposure to vapor or mists may cause moderate to severe irritation of the respiratory tract.			
Carcinogenicity:	NTP	IARC monographs	OSHA Regulated
	1	Not listed	Not regulated
Signs and Symptoms of Exposure: Eye Contact: a stinging sensation, excess blinking and tear production, redness and swelling of the conjunctive. Skin Contact: redness and a burning sensation. Prolonged or widespread contact may result in the absorption of potentially harmful amounts of material, with identical symptoms as ingestion. Ingestion: nausea, headache, dizziness, and abdominal pain. Inhalation: headache, nausea, coughing, chest pain and vomiting.			
Medical Conditions Generally Aggravated by Exposure		None known	
Emergency and First Aid Procedures Inhalation-remove victim to fresh air and seek medical attention if irritation persists. Eyes-immediately flush exposed areas with large quantities of water for at least 15 minutes. Skin- immediately flush skin with large amounts of water for at least 15 minutes while removing contaminated clothing. If irritation is evident or discoloration persists, seek medical attention. Ingestion-do not induce vomiting unless directed by medical personnel. Drink large quantities of water or milk. Seek medical attention.			

Section VII-Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled	Remove any source of ignition. Dike spill using soil, sand, or absorbent. Soak up with suitable, non-combustible absorbent material, collect in suitable containers for disposal. Recover free product, if possible. Prevent flow to sewer and public waters. For water spill, notify downstream users of possible contamination.
Waste Disposal Method	Dispose of in accordance with all Local, State and Federal regulations.
Precautions to Be Taken in Handling and Storing	Store at temperatures between 32 ⁰ F-110 ⁰ F, keep container tightly closed. Empty containers should be thoroughly rinsed with water and disposed of according to local regulations.

Section VIII-Control Measures

Respiratory Protection (Specify Type) Use NIOSH approved chemical cartridge (organic vapor) respiratory equipment when spraying material (full face respirator is recommended)			
Ventilation	Local Exhaust	Sufficient to maintain air concentration as required by OSHA	Special N/A
	Mechanical (General)	Maintain adequate ventilation	Other N/A
Protective Gloves	Butyl rubber, Neoprene gloves	Eye Protection	Eye protection for application and removal such as chemical splash goggles.
Other Protective Clothing or Equipment Impervious coveralls, apron, boots, as necessary to prevent skin contact. Eye wash as needed.			

N/A = Not applicable

Section IX-Additional Information

This product does not contain any chemicals that are reportable under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

TRANSPORTATION: Not regulated.