Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U. S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List) Multi-Strip Professional Paint Remover	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.		
Section I			
Manufacturer's NameManufacturer's Code: 657Sunnyside CorporationSundation	Emergency Telephone NumberChem Trec(800) 424-9300		
Address (Number, Street, City, and ZIP Code) 225 Carpenter Avenue Wheeling, IL 60090	Telephone Number for Information (847) 541-5700		
	Date Prepared 06/24/09		
	Signature of Preparer (optional)		
Section II-Hazardous Ingredients/Identity Information			

Hazardous Components (Specific Chemical Identity; Common Name(s)) OSHA PEL ACGIH TLV Other Limits % (optional)

N.Methyl-2 Pyrrolidone (872-50-4)	Not Established	15-35%
Dimethyl Glutarate (1119-40-0)	Not Established	20-35%
Dimethyl Adipate (627-93-0)	Not Established	5-10%
Dimethyl Succinate (106-65-0)	Not Established	5-15%
Formic Acid (64-18-6)	5 PPM 5 PPM (10 PPM STEL)	1-2%
Non Toxic/Non Hazardous Components	N/A	20-40%

Section III- Physical/Chemical Characteristics

Boiling Point	205 ⁰ F	Specific Gravity (H ₂ 0=1)	1.14
Vapor Pressure (mm Hg.) at 20 $^{\circ}$ C (68 $^{\circ}$ F)	0.2mm Hg	Melting Point	N/A
Vapor Density (AIR =1)	>1.0	Evaporation Rate (Butyl Acetate=1)	<1
Solubility in Water Partial			

Appearance and Odor Creamy Gel with mild odor

Section IV- Fire and Explosion Hazard Data

95 [°] C Seta Flash	Flammable Limits	LEL	1.3	UEL	9.5
Water fog, spray, dry chemical $C0_2$					
Special Fire Fighting Procedures Do not enter confined fire space without protective equipment including NIOSH approved SCBA.					
Use water spray to cool fire exposed surfaces and to protect personnel.					
Unusual Fire and Explosion Hazards Vapor is explosive at air temperatures higher than the flash point.					
Health 1 Flammability 1 Reactivity 0					
N/A = Not Applicable					
	Water fog, spray, de Do not enter confine Use water spray to c rds Vapor is explose	Water fog, spray, dry chemical C0 ₂ Do not enter confined fire space without protective equipment Use water spray to cool fire exposed surfaces and to protect pe rds Vapor is explosive at air temperatures higher than the flas	Water fog, spray, dry chemical C0 ₂ Do not enter confined fire space without protective equipment including Use water spray to cool fire exposed surfaces and to protect personnel. rds Vapor is explosive at air temperatures higher than the flash point.	Water fog, spray, dry chemical C02 Do not enter confined fire space without protective equipment including NIOSH Use water spray to cool fire exposed surfaces and to protect personnel. rds Vapor is explosive at air temperatures higher than the flash point.	Water fog, spray, dry chemical C02 Do not enter confined fire space without protective equipment including NIOSH approve Use water spray to cool fire exposed surfaces and to protect personnel. rds Vapor is explosive at air temperatures higher than the flash point.

Section V-React	tivity Data					
Stability	Unstable		Conditions to Avoid	Strong oxidizing agents	s, fire, flame	
	Stable	Х				
Incompatibility (M	aterials to Avoid)	Strong c	exidizers, acid and alkalis			
Hazardous Decom	position or Byproduc	ts Unlikely	ý			
Hazardous Polymerization	May Occur		Conditions to Avoid	Keep away from heat, spa	arks and open flame.	
	Will Not Occur	Х				
	lth Hazard Data					
Route (s) of Entry:						
				owsiness, and nausea, and m	ay lead to	
	ightly irritating to the			1 .		
Ingestion: Extreme	levels can cause nause	a, headache a	nd vomiting, or higher leve	els may cause unconsciousne	ess.	
•	May cause eye irritatio					
				or may cause slight to mode		
		, vapors or mi	sts may cause slight skin ii	ritation. Ingestion may cause	se moderate to	
severe irritation of t Carcinogenicity:		TP? NO	IARC monog	raphs? NO OSHA Re	egulated? NO	
			on unlikely to reach expos	•	guiateu. 110	
· · ·	s Generally Aggravat	•		••••		
				appropriate personal protec	tive equipment	
	on to fresh air. Remove			appropriate personal protee	tive equipment.	
				tim at rest in half upright po	sition. If not	
	icial respiration. Obtain					
Ingestion: If swallo	wed, rinse mouth with	water (only if	person is conscious). Seel	medical attention.		
				es. Obtain medical attention	if symptoms occur.	
Eye Contact: Rinse with plenty of running water. Obtain medical attention if symptoms occur. Section VII-Precautions for Safe Handling and Use						
		0		hla non ranativa absorbant	material collect in	
Steps to Be Taken in Case Material is Released or Spilled Soak up with suitable, non-reactive absorbent material, collect in suitable containers for disposal.						
Waste Disposal Method Dispose of in accordance with all local, state and federal regulations.						
Precautions to Be Taken in Handing and Storing Store at temperatures between $40^{\circ}F - 95^{\circ}F$						
Section VIII Control Magnung						
Section VIII-Control Measures Provide The American Structure American						
	Respiratory Protection (Specify Type)Wear filter mask, filter type AVentilationLocal ExhaustUse with adequate ventilationSpecial			N/A		
		-	referred and recommended	Other	N/A	
	Mechanical (General) Exhaust pi	eleffed and recommended	Other	IN/A	
Protective Gloves Neoprene gloves Eye Protection Safety glasses with side shield						
Other Protective Clothing or Equipment Filter mask, filter type A						
N/A = Not applicable						
i ot uppnouo	· • ·					

Section IX-Additional Information

This product contains the following toxic chemicals which are subject to reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

TOXIC CHEMICAL	CAS #	APPROXIMATE % BY WEIGHT		
N-Methyl-2-Pyrrolidone Formic Acid	872-50-4 64-18-6	25.7% 1.7%		
SARA Title III Hazard Categories:	Immediate (Act	ute) Health Hazard		
TRANSPORTATION: Not regulated as DOT Hazardous Material.				
California Proposition 65: This product contains N-Methyl Pyrrolidone, a chemical known to the state of California to cause birth				

defects or other reproductive harm.