Product Number 476

SAFETY DATA SHEET

Issuing Date 06-May-2015 Revision Date 05/28/15 Revision Number 3



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Low VOC General Purpose Thinner

Other means of identification

UN-No. UN1263

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Solvent mixture

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Sunnyside Corporation

Supplier Address 225 Carpenter Avenue

Wheeling IL 60090 US

Supplier Phone Number Phone:8475415700

Fax:8475419043

Supplier Email sscontact@sunnysidecorp.com

Emergency telephone number Chem Trec 800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B



Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal word

Danger

Hazard Statements
Causes serious eye irritation
May cause genetic defects
May cause drowsiness or dizziness
Highly flammable liquid and vapor

Appearance Clear

Physical state Liquid

Odor Pungent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Wear eye/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction



Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION Exposure to chlorinated hydrocarbons, such as chloroform and trichloroethane, may increase toxic effects INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No	Weight-%	Trade Secret
Acetone	67-64-1	60 - 100	
Aliphatic Naphtha	64742-89-8	1 - 5	

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention

if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, (trained personnel should) give oxygen.

Ingestion Rinse mouth immediately and drink plenty of water. Never give anything by mouth

to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take

precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

Burning sensation. Inhalation of high vapor concentrations may cause symptoms

like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO2, water spray or regular foam. Use water spray or fog; do not use straight streams.

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

<u>Specific hazards arising from the chemical</u> Some may be transported hot.

Uniform Fire Code Flammable Liquid: I-B

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.



6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Ensure adequate ventilation. Evacuate personnel to safe areas. See section 8 for more information. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

material.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth,

sand or other non-combustible material and transfer to containers.

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for

later disposal. Soak up with inert absorbent material. Pick up and transfer to properly

labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to

package label instructions.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with

the particular national regulations. Store in accordance with local regulations.

Incompatible Products Strong oxidizing agents. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters



Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm 10% LEL
	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	_
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors	
		(vacated) STEL: 1000 ppm	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection None required for consumer use. If splashes are likely to occur:. Tight sealing safety

goggles.

Skin and body protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant

apron. Impervious gloves. Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Liquid Appearance Clear

AppearanceClearOdorPungentColorNo information availableOdor ThresholdNo information available

Property Values Remarks Method

pHUNKNOWNNone knownMelting / freezing pointNo data availableNone knownBoiling point / boiling range56 °C / 133 °FNone knownFlash Point0 FNone knownEvaporation RateNo data availableNone known



Flammability (solid, gas) No data available None known

Flammability Limit in Air

Upper flammability limit No data available Lower flammability limit No data available

Vapor pressure No data available None known Vapor density No data available None known **Specific Gravity** No data available None known Water Solubility Completely soluble None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known No data available **Autoignition temperature** None known None known **Decomposition temperature** No data available Kinematic viscosity No data available None known **Dynamic viscosity** No data available None known

Explosive properties No data available **Oxidizing properties** No data available

Other Information

Softening Point No data available No data available **VOC Content (%)** No data available **Particle Size**

Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. May cause drowsiness and dizziness.

Specific test data for the substance or mixture is not available. Expected to be an irritant Eye contact

based on components. May cause redness, itching, and pain. May cause temporary eye

irritation.

Skin contact Specific test data for the substance or mixture is not available. May cause irritation.



Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	-	-	= 50100 mg/m³ (Rat) 8 h
Aliphatic Naphtha	-	= 3000 mg/kg(Rabbit)	-

Information on toxicological effects

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects Contains a known or suspected mutagen.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic ToxicityContains a known or suspected mutagen. Possible risk of irreversible effects.

Target Organ Effects Eyes. May affect the genetic material in germ cells (sperm and eggs). Central Nervous

System (CNS). Respiratory system. Skin. Blood.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist)

103.20 mg/l



12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Acetone		96h LC50: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) 96h LC50: 6210 - 8120 mg/L (Pimephales promelas) 96h LC50: = 8300 mg/L (Lepomis macrochirus)		48h EC50: 10294 - 17704 mg/L 48h EC50: 12600 - 12700 mg/L
Aliphatic Naphtha	72h EC50: = 4700 mg/L (Pseudokirchneriella subcapitata)			

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Aliphatic Naphtha	-0.24

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Acetone	Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No. UN1263
Proper Shipping Name PAINT



Hazard Class 3 **Packing Group** Ш

Description UN1263, PAINT, 3, II

Emergency Response Guide

Number

TDG

UN1263 UN-No. **Proper Shipping Name PAINT** Hazard Class 3 **Packing Group** Ш

Description UN1263, PAINT, 3, II

MEX

UN-No. UN1263 **Proper Shipping Name PAINT Hazard Class** 3 **Packing Group**

Description UN1263, PAINT, 3, II

ICAO

UN-No. UN1263

Proper Shipping Name PAINT RELATED MATERIAL

Hazard Class 3 **Packing Group** Ш

Description UN1263, PAINT RELATED MATERIAL, 3, II

IATA

UN1263 UN-No.

Proper Shipping Name PAINT RELATED MATERIAL

Hazard Class 3 **Packing Group**

Description UN1263, PAINT RELATED MATERIAL, 3, II

IMDG/IMO

UN-No. UN1263 **Proper Shipping Name** PAINT **Hazard Class** 3 **Packing Group** Ш EmS-No. F-E, S-E

Description UN1263, PAINT, 3, II, (0°C C.C.)

RID

UN-No. UN1263 PAINT **Proper Shipping Name Hazard Class** 3 **Packing Group** Ш Classification code F1

Description UN1263, PAINT, 3, II

ADR

UN1263 UN-No. **Proper Shipping Name PAINT Hazard Class** 3 **Packing Group** Ш Classification code F1 **Tunnel restriction code** (D/E)

Description UN1263, PAINT, 3, II

<u>ADN</u>



UN-No. UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group II
Classification code F1

Special Provisions 163, 640C, 650 Description UN1263, PAINT, 3, II

Hazard Labels 3
Limited Quantity 5 L
Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Acetone		Х		Х	

International Regulations



Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Acetone		Mexico: TWA= 1000 ppm
(60 - 100)		Mexico: TWA= 2400 mg/m ³
		Mexico: STEL= 1260 ppm
		Mexico: STEL= 3000 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada WHMIS Hazard Class B2 - Flammable liquid D2B - Toxic materials



16. OTHER INFORMATION

NFPA Health Hazards 2 Flammability 3 Instability 0 Physical and Chemical Hazards - HMIS Health Hazards 2 * Flammability 3 Physical Hazard 0 Personal Protection

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date 06-May-2015 **Revision Date** 06-May-2015

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

