

SAFETY DATA SHEET

Product Number 477

Issuing Date No data available

Revision Date 05/29/15

Revision Number 3



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Sunnyside VOC Compliant Lacquer Thinner

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Thinning Lacquers

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Sunnyside Corporation
Supplier Address 225 Carpenter Avenue
Wheeling
IL
60090
US
Supplier Phone Number Phone:8003238611
Fax:8475419043
Supplier Email sscontact@sunnysidecorp.com
Emergency telephone number Chem Trec 8004249300

2. HAZARDS IDENTIFICATION

Classification


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Flammable liquids	Category 2



GHS Label elements, including precautionary statements

Emergency Overview

Signal word	Danger
Hazard Statements Harmful if swallowed Harmful in contact with skin Harmful if inhaled Causes skin irritation Causes serious eye irritation Highly flammable liquid and vapor	
	
Appearance Clear	Physical State Liquid
Odor Acetic	

Precautionary Statements - Prevention

- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Wear protective gloves/protective clothing/eye protection/face protection
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating/ lighting/ equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Skin

- Call a POISON CENTER or doctor/physician if you feel unwell
- If skin irritation occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell

Ingestion

- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
- Rinse mouth

Fire

- In case of fire: Use CO2, dry chemical, or foam for extinction



Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Toxic to aquatic life with long lasting effects

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Exposure to chlorinated hydrocarbons, such as chloroform and trichloroethane, may increase toxic effects

INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Acetone	67-64-1	60 - 100	
Parachlorobenzotrifluoride	98-56-6	3 - 7	
2-Butoxyethanol	111-76-2	1 - 5	

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice

Show this safety data sheet to the doctor in attendance.

Eye Contact

If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area.

Skin Contact

If symptoms persist, call a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.



Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO2, water spray or regular foam. Use water spray or fog; do not use straight streams.

Unsuitable Extinguishing Media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Some may be transported hot.

Uniform Fire Code	Flammable Liquid: I-B Irritant: Liquid Highly Toxic: Liquid
--------------------------	-------------------------------------------------------------------

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.



6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Avoid breathing vapors or mists. Evacuate personnel to safe areas. See section 8 for more information. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental Precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use with local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid breathing vapors or mists. Use personal protection equipment. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Protect from moisture. Store locked up. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION



Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Parachlorobenzotrifluoride	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	
Acetone	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Tight sealing safety goggles. If splashes are likely to occur: Face protection shield.

Skin and Body Protection

Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties



Physical State	Liquid	Odor	Acetic
Appearance	Clear	Odor Threshold	No information available
Color	Water White		

<u>Property</u>	<u>Values</u>	<u>Remarks/ Method</u>
pH	Unknow	None known
Melting / freezing point	No data available	None known
Boiling point / I.B.P.	133 °F	None known
Flash Point, T.C.C. °F	0	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Partially soluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	

Other Information

Softening Point	No data available
VOC Content (g/L)	24 g/L
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat. Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION



Information on likely routes of exposure

Product Information

- Inhalation** Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).
- Eye Contact** Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation.
- Skin Contact** Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation. May be absorbed through the skin in harmful amounts. Harmful in contact with skin. (based on components).
- Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed. (based on components).

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butoxyethanol	= 470 mg/kg (Rat)	= 220 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
Parachlorobenzotrifluoride	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
Acetone	-	-	= 50100 mg/m ³ (Rat) 8 h

Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

- Sensitization** No information available.
- Mutagenic Effects** No information available.
- Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol	A3	Group 3		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

- Reproductive Toxicity** No information available.
- STOT - single exposure** No information available.
- STOT - repeated exposure** No information available.



Chronic Toxicity No known effect based on information supplied. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Carcinogenic potential is unknown.

Target Organ Effects Respiratory system. Eyes. Skin. Blood. Central Nervous System (CNS). Hematopoietic system. Kidney. Liver.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

- ATEmix (oral)**
510.00 mg/kg
- ATEmix (dermal)**
1,196.00 mg/kg (ATE)
- ATEmix (inhalation-dust/mist)**
2.00 mg/l
- ATEmix (inhalation-vapor)**
12.00 ATEmix

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT

Ecotoxicity
Toxic to aquatic life with long lasting effects.

Persistence and Degradability
No information available.

Bioaccumulation
No information available

Chemical Name	Log Pow
2-Butoxyethanol	0.81
Acetone	3.7
Parachlorobenzotrifluoride	-0.24

Other adverse effects
No information available.



13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
2-Butoxyethanol		Included in waste stream: F039		U002

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Acetone	Ignitable

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY
Hazard Class ORM-D
Marine Pollutant This product contains a chemical which is listed as a marine pollutant according to DOT
Description CONSUMER COMMODITY, ORM-D, NONE
Emergency Response Guide Number 128

TDG

UN-No. UN1263
Proper Shipping Name PAINT RELATED MATERIAL
Hazard Class 3
Packing Group II
Description UN1263, PAINT RELATED MATERIAL, 3, II

MEX

UN-No. UN1263
Proper Shipping Name PAINT RELATED MATERIAL
Hazard Class 3
Packing Group II
Description UN1263, PAINT RELATED MATERIAL, 3, II

ICAO

UN-No. UN1263
Proper Shipping Name PAINT RELATED MATERIAL
Hazard Class 3
Packing Group II
Description UN1263, PAINT RELATED MATERIAL, 3, II

IATA

UN-No. UN1263
Proper Shipping Name PAINT RELATED MATERIAL



Hazard Class 3
Packing Group II
Description UN1263, PAINT RELATED MATERIAL, 3, II

IMDG/IMO

UN-No. UN1263
Proper Shipping Name PAINT RELATED MATERIAL
Hazard Class 3
Packing Group II
EmS No. F-E, S-E
Description UN1263, PAINT RELATED MATERIAL, 3, II, (-18°C C.C.)

RID

UN-No. UN1263
Proper Shipping Name PAINT RELATED MATERIAL
Hazard Class 3
Packing Group II
Classification code F1
Description UN1263, PAINT RELATED MATERIAL, 3, II

ADR

UN-No. UN1263
Proper Shipping Name PAINT RELATED MATERIAL
Hazard Class 3
Packing Group II
Classification code F1
Tunnel restriction code (D/E)
Description UN1263, PAINT RELATED MATERIAL, 3, II

ADN

UN-No. UN1263
Proper Shipping Name PAINT RELATED MATERIAL
Hazard Class 3
Packing Group II
Classification code F1
Special Provisions 163, 640C, 650
Description UN1263, PAINT RELATED MATERIAL , 3, II
Limited Quantity 5 L
Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL All components are listed either on the DSL or NDSL.
IECSC -

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Glycol Ethers (Ethylene Glycol Mono Butyl Ether)	111-76-2	1 - 5	1.0



SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
2-Butoxyethanol	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
2-Butoxyethanol	X	X	X	X	X
Parachlorobenzotrifluoride		X		X	

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Acetone (60 - 100)		Mexico: TWA 26 ppm Mexico: TWA 120 mg/m ³ Mexico: STEL 75 ppm Mexico: STEL 360 mg/m ³
2-Butoxyethanol (1 - 5)		Mexico: TWA= 1000 ppm Mexico: TWA= 2400 mg/m ³ Mexico: STEL= 1260 ppm Mexico: STEL= 3000 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

B2 - Flammable liquid

D2B - Toxic materials





16. OTHER INFORMATION

NFPA	Health Hazards 2	Flammability 3	Instability 0	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazards 2	Flammability 3	Physical Hazard 0	

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Revision Date 17-Sep-2014

Revision Note No information available

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

