

Product Number 637

SAFETY DATA SHEET

Issuing Date No data available

Revision Date 21-Jan-2015

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name 2-Minute Remover Aerosol

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Paint or Varnish Remover (Paint or Paint-Related)

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Sunnyside Corporation
Supplier Address 225 Carpenter Avenue
Wheeling
IL
60090
US
Supplier Phone Number Phone:800-323-8611
Fax:8475419043
Supplier Email sscontacts@sunnysidecorp.com
Emergency telephone number Chem Trec 800-424-9300

2. HAZARDS IDENTIFICATION

Classification


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1
Flammable gases	Category 1
Gases under pressure	Compressed gas

GHS Label elements, including precautionary statements



Emergency Overview

Signal word	Danger	
Hazard Statements		
Harmful if swallowed		
May cause cancer		
Causes damage to organs		
Extremely flammable gas		
Contains gas under pressure; may explode if heated		
		
Appearance	Opaque	Physical State Liquid spray Aerosol
		Odor Pungent

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician
 Specific treatment (see supplemental first aid instructions on this label)

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 Rinse mouth

Fire

Leaking gas fire: Do not extinguish, unless leak can be stopped safely
 Eliminate all ignition sources if safe to do so

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place
 Protect from sunlight. Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
2-Butoxyethanol	111-76-2	0 - 5	
Dichloromethane	75-09-2	40 - 70	
Butane (propellant)	106-97-8		
Propane (propellant)	74-98-6		
Methyl alcohol	67-56-1	5 - 20	

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures**General Advice**

Show this safety data sheet to the doctor in attendance.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

Skin Contact

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects No information available.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO₂).

Unsuitable extinguishing media

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific Hazards Arising from the Chemical

Ruptured cylinders may rocket. Some may burn but none ignite readily.

Uniform Fire Code

Aerosols: Level III

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact Yes.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Stop leak if you can do it without risk.

Other Information

Ventilate the area.

Environmental Precautions

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment

If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

Methods for cleaning up

Do not direct water at spill or source of leak.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Avoid contact with eyes. Keep away from open flames, hot surfaces and sources of ignition.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up. Protect from sunlight.

Incompatible Products

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Dichloromethane 75-09-2	TWA: 50 ppm	TWA: 25 ppm Action Level: 12.5 ppm See 29 CFR 1910.1052 (vacated) TWA: 500 ppm (vacated) STEL: 2000 ppm 5 min in any 3 h (vacated) Ceiling: 1000 ppm STEL: 125 ppm see 29 CFR 1910.1052	IDLH: 2300 ppm
Supplier Trade Secret	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³
Supplier Trade Secret	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 325 mg/m ³ STEL: 250 ppm

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection	If splashes are likely to occur: Wear safety glasses with side shields (or goggles).
Skin and Body Protection	Wear protective gloves and protective clothing.
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Liquid spray, Aerosol	Odor	Pungent
Appearance	Opaque	Odor Threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	UNKNOWN	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Slightly soluble	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing Properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye Contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin Contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available. Harmful if swallowed. (based on components). May cause central nervous system depression.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Dichloromethane 75-09-2	= 1600 mg/kg (Rat)	-	= 53 mg/L (Rat) 6 h = 76000 mg/m ³ (Rat) 4 h
Supplier Trade Secret	-	-	= 658 g/m ³ (Rat) 4 h
Supplier Trade Secret	-	-	= 658 mg/L (Rat) 4 h
Methyl alcohol 67-56-1	= 5628 mg/kg (Rat)	-	= 83.2 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Dichloromethane 75-09-2	A3	Group 2A	Reasonably Anticipated	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity No information available.

STOT - single exposure Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Causes damage to organs if swallowed.

STOT - repeated exposure No information available.

Chronic Toxicity No known effect based on information supplied. May cause adverse liver effects. Contains a known or suspected carcinogen. Effects from this product caused by acute exposure may cause permanent damage to target organs and/or may cause chronic conditions.

Target Organ Effects Central Nervous System (CNS). Central Vascular System (CVS). Eyes. Gastrointestinal tract (GI). Liver. Lungs. Respiratory system. Skin. Endocrine system. Systemic Toxicity.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

1,453.00 mg/kg

ATEmix (dermal)

11,029.00 mg/kg (ATE)

ATEmix (inhalation-dust/mist)

18.42 mg/l

ATEmix (inhalation-vapor)

110.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Dichloromethane 75-09-2	96h EC50: > 500 mg/L (Pseudokirchneriella subcapitata) 72h EC50: > 500 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 140.8 - 277.8 mg/L (Pimephales promelas) 96h LC50: 262 - 855 mg/L (Pimephales promelas) 96h LC50: = 193 mg/L (Lepomis macrochirus)	EC50 = 1 mg/L 24 h EC50 = 2.88 mg/L 15 min	48h EC50: 1532 - 1847 mg/L 48h EC50: = 190 mg/L
Methyl alcohol 67-56-1		96h LC50: = 28200 mg/L (Pimephales promelas) 96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 19500 - 20700 mg/L (Oncorhynchus mykiss) 96h LC50: 18 - 20 mL/L (Oncorhynchus mykiss) 96h LC50: 13500 - 17600 mg/L (Lepomis macrochirus)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Dichloromethane 75-09-2	1.25
Supplier Trade Secret	2.89
Supplier Trade Secret	2.3
Methyl alcohol 67-56-1	-0.77

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Dichloromethane 75-09-2	waste number U080	Included in waste streams: F001, F002, F024, F025, F039, K009, K010, K156, K157, K158		U080
Methyl alcohol 67-56-1		Included in waste stream: F039		U154

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Dichloromethane 75-09-2	Category I - Volatiles		Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Dichloromethane 75-09-2	Toxic
Methyl alcohol 67-56-1	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY
Hazard Class 2.1
Description UN1950, AEROSOLS, 2.1
Emergency Response Guide Number 126

TDG

UN-No. UN1950



Proper Shipping Name AEROSOLS
Hazard Class 2.1
Subsidiary class 6.1
Description UN1950, AEROSOLS, 2.1 (6.1)

MEX

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Description UN1950, AEROSOLS MIXTURE, 2.1

ICAO

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Subsidiary class 6.1
Description UN1950, AEROSOLS, 2.1 (6.1)

IATA

UN-No. UN1950
Proper Shipping Name AEROSOLS, FLAMMABLE, CONTAINING SUBSTANCES IN DIVISION 6.1, PACKING GROUP III
Hazard Class 2.1
Subsidiary class 6.1
Description UN1950, AEROSOLS, FLAMMABLE, CONTAINING SUBSTANCES IN DIVISION 6.1, PACKING GROUP III, 2.1 (6.1)

IMDG/IMO

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Subsidiary class 6.1
EmS-No. F-D, S-U
Description UN1950, AEROSOLS, 2.1

RID

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Classification code 5TF
Description UN1950, AEROSOLS, 2.1 (6.1)
ADR/RID-Labels 6.1

ADR

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Classification code 5TF
Tunnel restriction code (D)
Description UN1950, AEROSOLS, 2.1 (6.1)
ADR/RID-Labels 6.1

ADN

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.1
Classification code 5TF
Special Provisions 190, 327, 344, 625
Description UN1950, AEROSOLS, 2.1 (6.1)
Hazard Labels 6.1

Limited Quantity 120 ML
Ventilation VE01, VE02, VE04

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Glycol Ethers (Ethylene Glycol Monbutyl Ether)	111-76-2	.5 -5	0.1
Dichloromethane - 75-09-2	75-09-2	40 - 70	0.1
Methyl alcohol - 67-56-1	67-56-1	1 - 5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden release of pressure hazard Yes
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Dichloromethane 75-09-2		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Dichloromethane 75-09-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Methyl alcohol 67-56-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Dichloromethane - 75-09-2	Carcinogen
Methyl alcohol - 67-56-1	Developmental

U.S. State Right-to-Know Regulations



Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Dichloromethane 75-09-2	X	X	X	X	X
Propane 74-98-6	X	X	X		
Butane 106-97-8	X	X	X		
Methyl alcohol 67-56-1	X	X	X	X	X
Glycol-Ether 111-76-2	X	X	X	X	X

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Dichloromethane 75-09-2 (40 - 70)	A3	Mexico: TWA 100 ppm Mexico: TWA 330 mg/m ³ Mexico: STEL 500 ppm Mexico: STEL 1740 mg/m ³
Propane 74-98-6 (10 - 30)		Mexico: TWA 800 ppm Mexico: TWA 1900 mg/m ³
Methyl alcohol 67-56-1 (1 - 5)		Mexico: TWA= 200 ppm Mexico: TWA= 260 mg/m ³ Mexico: STEL= 250 ppm Mexico: STEL= 310 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens
A3 - Confirmed Animal Carcinogen

Canada

WHMIS Hazard Class

- A - Compressed gases
- B5 - Flammable aerosol
- D2A - Very toxic materials



16. OTHER INFORMATION

NFPA	Health Hazards 2	Flammability 3	Instability 0	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazards 2*	Flammability 3	Physical Hazard 0	

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Revision Date 21-Jan-2015

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet