



**Product Number: 622**

**Product Name: Paint DeGlosser And Pre-Paint Cleaner**

## **USE AND SAFETY INFORMATION**

**Directions:** Rubber gloves and eye protection are recommended. It is preferable to degloss a small area and allow it to dry thoroughly. This small test area can be used to determine whether more or less application pressure is needed. A rag or paper towel may be used as a deglossing applicator on most surfaces; the use of steelwool may be more abrasive than necessary. When using steelwool as an applicator, use fine or extra fine, applying only enough pressure to etch the surface slightly. For indoor use on large surface areas, apply to an area no greater than 8 ft. by 10 ft. After surface has been deglossed, wipe it with a damp, lint-free rag or paper towels. Before painting, surface must be clean and free of any dirt or debris. Allow at least 10 minutes before repainting deglossed surfaces.

**CAUTIONS:** CONTAINS SODIUM META SILICATE. Harmful if swallowed. May cause eye or skin irritation. Do not take internally. Avoid contact with eyes or prolonged contact with skin. Close container after each use. Do not transfer to unlabeled containers.

**First Aid:** CONTAINS SODIUM META SILICATE. Harmful if swallowed. May cause eye or skin irritation. Do not take internally. Avoid contact with eyes or prolonged contact with skin. Close container after each use. Do not transfer to unlabeled containers.

**KEEP OUT OF REACH OF CHILDREN.**

VOC: 0