



Product Number: 662

Product Name: Ready-Strip Professional Strength Paint Remover

USE AND SAFETY INFORMATION

*Capable of removing up to 10 layers in a single application using a stripping tool.

- Biodegradable • Non-Flammable • Low Odor • Water Clean-up
- No drip formula clings to vertical surfaces and completely fills detailed areas.
- Use on interior or exterior surfaces including wood, plaster, concrete, brick, stone, masonry, marble, metal and veneers. DO NOT use on sheetrock, plastic, rubber or linoleum surfaces) Stir only. **DO NOT SHAKE. DO A TEST AREA FIRST TO DETERMINE RESULTS.**

Directions: Mask any areas not being stripped with plastic and masking tape. Apply READY-STRIP Pro liberally to the surface with a brush, medium sized nap paint roller, or putty knife so that the remover completely masks or covers the color of the surface to be stripped. **Do not brush out too thin like a coat of paint.** Coverage is approximately 50 sq. ft. per gallon. Apply at temperatures between 60° F and 80° F. When the stripper turns off-white, it may form an eggshell like skin to lock in the stripping action. Misting the area to be removed with water or READY-STRIP Paint Remover Wash prior to actual removal will soften the skin and make lifting of the paint or varnish easier. After the stripper has turned off-white, *use a paint scraper to lift paint from flat surfaces or a stiff bristle brush for detailed areas. After initial lifting, use a nylon bristle brush or stripping pad to scrub surface. The time the stripper takes to turn off-white may vary depending upon the type and amount of paint, the surface and temperature. Typical color change usually occurs within 4–24 hours. Paint or varnish removal may take place prior to the Color Change, although the Color Change will indicate the end of stripping action. Apply READY-STRIP Paint Remover Wash or light amounts of water for final clean up of residue. Surface should be completely dry before repainting. No need to neutralize (acid wash) surface. Clean tools after use with soap and water. Use a combination of READY-STRIP Pro & READY-STRIP Paint Remover Wash with scrub pad to lift stain.

Removal Time: On interior surfaces, the softened paint/varnish may remain moist under the eggshell skin for several days for easy removal. On exterior surfaces, due to the potential for higher temperatures and direct sunlight, the Color Change may be greatly accelerated (1–8 hours). The paint should be removed shortly after Color Change to prevent the stripper from drying out. Not advisable for outdoor decks.

Hints: If READY-STRIP Pro is applied too thinly, left on too long, or due to excessive heat conditions, the applied area is difficult to scrape, try the following: 1) Mist the applied area with water or READY-STRIP Wash, wait 5-15 minutes and remove; 2) Reapply READY-STRIP Pro over itself, wait 15-30 minutes and remove; 3) if 1) or 2) does not work, scrape off and reapply. If product freezes in bucket, let thaw and stir vigorously until consistent.

CAUTION: CONTAINS N-METHYL-2-PYRROLIDONE, BENZYL ALCOHOL, AND FORMIC ACID. Do not transfer to unlabeled containers. May cause eye and skin irritation on contact. Close container after use.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

SAFETY & FIRST AID: Rubber gloves and safety glasses are recommended for eye and skin protection. Avoid eye contact. If eye contact occurs, immediately flush with plenty of water for 15 minutes. Avoid prolonged and repeated contact with skin. If skin contact occurs, wash with soap and water. Do not take internally. If swallowed do not induce vomiting. Give 1 or 2 glasses of water and call a physician immediately. Provide adequate ventilation in confined areas or use NIOSH approved respirator.

KEEP OUT OF REACH OF CHILDREN.

California SCAQMD Rule 443.1: Max. VOC: 441 g/L; Max Vapor Pressure of VOC: 28.5 mm Hg. Non-photochemically Reactive. Less than 50% VOC.