



**Product Number: 665**

**Product Name: Tough-2-Strip Industrial Strength Remover**

## **USE AND SAFETY INFORMATION**

Tough-2-Strip™ safely removes the toughest paint or marine coatings in a single application.

- Strips 1 to 4 layers quickly or multiple layers over time.
- Biodegradable • User Friendly • Odorless • Industrial Strength
- Non-Flammable • Safer to Use • Easily Cleaned-Up with Water
- Contains NO Methylene Chloride, Caustic or Harsh Chemicals.
- Clings to vertical surfaces and completely fills detailed areas.
- Can be easily brushed, rolled or sprayed onto the surface.
- Removes most varieties of household paints, varnishes, latex, alkyds, stains, enamels, lacquers, clear paints as well as more difficult coatings such as epoxy and urethanes.
- Use on interior or exterior surfaces including wood, plaster, concrete, brick, stone, masonry, marble, metal and veneers (DO NOT use on sheetrock, plastic, rubber or linoleum surfaces).
- Will not damage fiberglass or a gel-coat.

**Hints:** Give the stripper the proper time to penetrate the layers or you defeat its purpose. Misting the area to be removed with water prior to removal may make lifting of the coating easier. If desired results are not achieved at first, leave stripper on longer if still wet, or apply a thicker coat. If still tacky and moist, reapply stripper over itself. If completely dry, scrape off and reapply. Product activity is reduced below a temp. of 60°F and may require additional dwell time before all layers of paint are removed.

**Boats:** Consult Marine Technical Data Sheet for detailed instructions

**CAUTIONS:** CONTAINS N-METHYL-2-PYRROLIDONE, DIBASIC ESTERS, AND FORMIC ACID. Do not transfer to unlabeled containers. May cause eye and skin irritation on contact. Close container after use.

**WARNING:** THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

**SAFETY & FIRST AID:** Rubber gloves and safety glasses are recommended for eye and skin protection. Avoid eye contact. If eye contact occurs, immediately flush with plenty of water for 15 minutes. Avoid prolonged and repeated contact with skin. If skin contact occurs, wash with soap and water. Do not take internally. If swallowed do not induce vomiting. Give 1 or 2 glasses of water and call a physician immediately. Provide adequate ventilation in confined areas or use NIOSH approved respirator.

## **KEEP OUT OF REACH OF CHILDREN.**

California SCAQMD Rule 443.1:Max. VOC 311 g/L; Max Vapor Pressure of VOC: 28.5 mm Hg. Non-photochemically Reactive. Less than 50% VOC.