



**Product Number: 702**

**Product Name: M-I Oil Based Paint Additive & Extender**

## USE AND SAFETY INFORMATION

### DIRECTIONS FOR USE WITH OIL BASED PAINTS

- Stir oil based paint thoroughly.
- Always check for compatibility by mixing small amount of additive with small amount of paint.
- If paint dries too fast and “drags”, stir in Sunnyside Oil Based Paint Additive beginning with one pint per gallon of paint.
- If needed, more Sunnyside Oil Based Paint Additive may be added (up to 2.5 pints per gallon paint).

### To condition bare or rusted metal:

- Remove loose rust, dirt and grease. Dry surface.
- Saturate metal with Sunnyside Oil Based Paint Additive.
- Allow 12-24 hours for drying.

### To condition fiberglass:

- Clean surface to be conditioned.
- Saturate a rag with Sunnyside Oil Based Paint Additive, wipe on surface.
- Buff surface with clean, soft cloth within 3 minutes.

For exterior use only.

Do not add to water based, acrylic or epoxy coatings.

**Directions:** Follow coating manufacturer’s instructions for thinning, using only recommended amounts. Do not use more than recommended, usually starting with a ratio of 4 ounces per gallon.

**Attention:** Do not attempt to start or re-ignite: charcoal, wood or any other fire with this product. An explosive fire may result or fire may flash back into the container and explode. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

**NOTE:** Addition of paint additive may raise coating VOC. Please check local and applicable VOC regulations before using Sunnyside Oil Based Paint Additive.

**CAUTIONS:** CONTAINS PETROLEUM DISTILLATE AND BOILED LINSEED OIL. Keep away from heat and flame. Do not use without fresh air ventilation. DO NOT smoke. Do not transfer to unlabeled containers. Close container after each use. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

**CAUTION:** RAGS, STEEL WOOL OR WASTE SOAKED WITH OIL BASED PAINT ADDITIVE MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER. The time frame and conditions under which materials may spontaneously catch fire are unpredictable. If rags or other application materials (including any materials containing oil based mixtures) are to be set aside, even for short periods of time, they should be placed in sealed, water-filled metal containers until final disposal.

**WARNING:** THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

**WARNING:** If you scrape, sand or remove old paint, you may release toxic dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log onto [www.epa.gov/lead](http://www.epa.gov/lead).

**First Aid:** If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly and get medical attention if irritation persists. If overcome by vapors, remove to fresh air and get medical attention.

Use only with adequate ventilation.

**KEEP OUT OF REACH OF CHILDREN.**