



Product Number: 722

Product Name: Gloss Remover Prepaint Cleaner

USE AND SAFETY INFORMATION

Directions: Rubber gloves and eye protection are recommended when using any solvent-based product. For indoor use on large surface areas, apply to an area no greater than 8 ft. by 10 ft. Use fine or extra fine steelwool as an applicator, applying only enough pressure to etch the surface slightly. It is preferable to degloss a small area and allow it to dry thoroughly. This small test area can be used to determine whether more or less application pressure is needed. After a large area has been deglossed, wipe it with a lint-free rag or paper towels to assist drying and remove any remaining steelwool dust. Allow at least 30 minutes before repainting deglossed surfaces. After using Gloss Remover Pre-Paint Cleaner, an oil-based paint or primer must be applied to the surface before using a latex coating. A rag or paper towel may be used as a deglossing applicator on some surfaces; the use of steelwool may be more abrasive than necessary. On very hard, high gloss surfaces, liquid should be applied to an 8 ft. by 10 ft. area with a rag or paper towel and allowed to stand for approximately two minutes before rubbing with steelwool. This method allows the Gloss Remover Pre-Paint Cleaner to soften the finish adequately to insure proper deglossing of very hard finishes such as lacquers, enamels and baked-on finishes.

CAUTIONS: CONTAINS DIPROPYLENE GLYCOL METHYL ETHER AND PETROLEUM DISTILLATE. Keep away from heat and open flame. Avoid contact with eyes and skin. Prolonged or repeated overexposure to all solvent vapors may be harmful to your health. Provide plenty of fresh air ventilation. Do not transfer to unlabeled containers. Close container after each use. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency.

Attention: Do not attempt to start or re-ignite: charcoal, wood or any other fire with this product. An explosive fire may result or fire may flash back into the can and explode. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly and get medical attention if irritation persists. If overcome by vapors, remove to fresh air and get medical attention.

Use only with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

California SCAQMD Rule 443.1: Max. VOC: 768 g/L; Max. Vapor Pressure of VOC: 1mm Hg; Non-Photochemically Reactive.