



Product Number: 822

Product Name: Xylol

USE AND SAFETY INFORMATION

Safety Note: Paints thinned with Xylene give off flammable vapors during drying. Always follow the coating manufacturer's directions and warnings, and be aware of the increased fire hazard when coating larger areas. If ventilation equipment is used, it must be explosion proof. If Xylene is used for any other purpose, limit flammable vapors by using only a few ounces at a time. Wait until all vapors are gone between uses. Read and follow all cautions on this label prior to using.

CAUTIONS: CONTAINS XYLENE AND ETHYLBENZENE. Keep away from heat, sparks and flame. Vapors are given off rapidly during use and may ignite explosively. Vapors are heavier than air and may travel long distances to other rooms or lower areas. DO NOT use in confined areas such as basements or bathrooms. Open all doors and windows to provide plenty of fresh air cross ventilation equal to outdoor conditions. DO NOT smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may linger for 30 minutes or more after use. If you smell Xylene, vapors are still present. Do not turn ignition sources on or relight pilot lights until certain that all vapors are gone. Avoid rubbing; friction may cause static electric sparks which may ignite vapors. For disposal guidance of unused product, contact a household hazardous waste program, or your local or state government environmental control agency. Do not transfer contents to unlabeled containers.

Attention: Do not attempt to start or re-ignite: charcoal, wood or any other fire with this product. An explosive fire may result or fire may flash back into the container and explode.

Health Hazards: Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Avoid breathing vapor or spray mist. Open doors and windows to provide plenty of fresh air ventilation during application and drying. If you experience eye watering, headaches, dizziness or have difficulty breathing, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area to obtain fresh air. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

First Aid: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly and get medical attention if irritation persists. If overcome by vapors, remove to fresh air and get medical attention.

Use only with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.